



VG3457CV - 34" UWQHD CURVED VIDEO CONFERENCING MONITOR WITH WINDOWS HELLO COMPATIBLE IR WEBCAM, 100W USB C, DOCKING


Key Features



34
DISPLAY



MVA
PANEL



3440 X 1440
RESOLUTION

Product Description

ViewSonic VG3457CV video conferencing monitor is an ultrawide docking monitor with premium features such as a Zoom certified pop-up webcam that will help maintain productive meetings whether in the office or working from home. Premium webcam features to improve visual and audio aspects of video calls such as built in LED lighting, and powerful speakers. The IR camera allows for secure and easy sign-on with Windows Hello. The 21:9 aspect ratio provides extra screen space, while the 1500R curved screen offers an immersive viewing experience. Reliable network connectivity is ensured with an integrated Ethernet port, and the latest USB Type-C connectivity provides up to 100W power delivery to your laptop. Additionally, the integrated USB hub allows for easy connecting and charging of peripherals and accessories.

Specifications

More Information	
UPC	766907026078
Screen Size	34
Viewable Area (in.)	34
Panel Type	MVA
Display Resolution	3440 x 1440
Display Resolution	UWQHD (3440x1440)
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	80,000,000:1
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	21:9
Response Time (Typical GTG)	5ms

Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	100Hz
PC Resolution (max)	3440 X 1440
Mac® Resolution (max)	3440 X 1440
USB Type A	4
USB Type C	100W x 1, 15W x 1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	35W
Eco Mode (optimized)	40W
Consumption (typical)	45W
Consumption (max)	210W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.0, DisplayPort, USB Type C: 30 ~ 150 KHz
Frequency Vertical	HDMI 2.0, DisplayPort, USB Type C: 48 ~ 100 Hz
Height Adjust	110 mm / 4.3 in
Swivel	120°
Tilt (Forward/Back)	5° / 40°
Net (lbs)	20.9
Net Without Stand (lbs)	15.4
Gross (lbs)	34.2
Net (kg)	9.5
Net Without Stand (kg)	7.0

Gross (kg)	15.5
Packaging (in.)	39 x 19.5 x 9.4
Physical (in.)	31.81 x 16.68~21.01 x 9.3
Physical Without Stand (in.)	31.81 x 15.4 x 4.53
Packaging (mm)	990.0 x 495.0 x 238.0
Physical (mm)	808.0 x 423.7~533.7 x 236.2
Physical Without Stand (mm)	808.0 x 31.3 x 4.53
Regulations	cTUVus, FCC-B ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy
Package Contents	VG3457CV Display, Power Cable, HDMI to HDMI Cable, USB Type-C Cable (with USB Type A adaptor), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907026078

Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 ☎

email: salesinfo@viewsonic.com ✉