


#### PA503S - 3800 LUMENS SVGA HOME WITH HDMI AND VERTICAL KEYSTONE

#### **Key Features**

#### REFURBISHED

- High brighness 3800 Lumens SVGA projector with advanced visual features
- 1.1x optical zoom, 40 degree vertical keystone for flexible setup
- A low 16ms input latency provides faster frame-by-frame action for smooth images without delay
- SuperEco Mode allows the lamp to shine bright for up to 15,000 hours
- Supports most media players, PCs, Macs, and mobile devices with inputs such as HDMI. VGA. mini USB





30 - 300 in. / 0.76 - 7.62 <sup>m</sup>PANEL



VGA (640 x 480) to WUXGA\_RB (1920 x 1200) RESOLUTION

Flexible connectivity for your favorite devices.



### Product **Description**

The ViewSonic® PA503S price-performance projector features 3,800 lumens, native SVGA 800 x 600 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503S also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503S is ideal for use in education and small business environments.
\*Energy consumption and lamp life may vary based on actual usage and other factors.

## **Specifications**

| UPC   | 766907904710                              |
|---|---|
| Light Source                                | DLP Lamp                                  |
| Display Resolution                          | SVGA (800x600)                            |
| Display Resolution                          | 800 x 600                                 |
| Brightness (Lumens)                         | 3,800 ANSI                                |
| Screen Size                                 | 30 - 300 in. / 0.76 - 7.62 m              |
| Throw Distance                              | 3.9 - 43 ft / 1.19 - 13.11 m              |
| Throw Ratio                                 | 1.96 ~ 2.15                               |
| Keystone                                    | Vertical (+/- 40°)                        |
| Lens  | 1.1x optical zoom                         |
| Light Source (watt)                         | 190                                       |
| Light Source Life, Normal (hours)           | 5000                                      |
| Light Source Life, Dynamic Eco-Mode (hours) | 15000                                     |
| Color Depth                                 | 1.07B Color (R/G/B 10bit)                 |
| Dynamic Contrast Ratio                      | 22,000:1                                  |
| Aspect Ratio                                | 4:3                                       |
| Input Lag                                   | 37ms                                      |
| Frequency Horizontal                        | 15K~102KHz                                |
| Frequency Vertical                          | 23~120Hz                                  |
| PC Resolution (max)                         | VGA (640 x 480) to WUXGA_RB (1920 x 1200) |
| Mac® Resolution (max)                       | VGA (640 x 480) to WUXGA_RB (1920 x 1200) |
| Mini USB Type B                             | 1   |
| 3.5mm Audio Out                             | 1   |
| 3.5mm Audio In                              | 1   |
| Control (RS232)                             | 1   |
| HDMI 1.4 In                                 | 1   |
| VGA In                                      | 2   |
| VGA Out                                     | 1   |
| Composite RCA Video In                      | 1   |
| Internal Speakers                           | 2W (x1)                                   |
| Voltage                                     | AC 100-240V (universal), 50-60Hz          |
| Consumption (typical)                       | 260W                                      |
| Stand-by                                    | <0.5W                                     |
| Temperature                                 | 32-104º F (0 - 40º C)                     |
| Net (lbs)                                   | 4.9                                       |
| Gross (lbs)                                 | 7.1                                       |

| Net (kg)         | 2.2  |
|------------------|--|
| Gross (kg)       | 3.2  |
| Packaging (in.)  | 14.4 × 7.4 × 11.8  |
| Physical (in.)   | 11.6 x 4.3 x 8.6   |
| Packaging (mm)   | 365 x 188 x 300  |
| Physical (mm)    | 294 x 110 x 218  |
| Regulations      | FCC (including ICES-003), cTUVus   |
| Package Contents | PA503S projector, power cable, VGA cable, remote control, Quick Start Guide  |
| Warranty         | Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws.   |

UPC: 766907904710









# Contact Sales ViewSonic.com

888.881.8781 email: salesinfo@viewsonic.com