

#### VP3881 - 38" CURVED ULTRA-WIDE WQHD+ COLORPRO™ IPS MONITOR W/ USB C

#### **Key Features**

- Immersive Curved Screen Design
- HDR10 Content Support
- Loaded with Connectivity (USB Type C, HDMI, DisplayPort, and HDCP 2.2)
- Amazing Color Accuracy
- Professional Color Processing Capability









3840 x 1600 **RESOLUTION** 



### Product **Description**

IPS

**PANEL** 

With an immersive curved screen and stunning WQHD+ 3840x1600 resolution, the ViewSonic® VP3881 monitor elevates your viewing experience from flat to panoramic. Delivering incredible detail and vivid colors across wide viewing angles, this monitor is engineered to provide incredible color accuracy, while HDR10 content support delivers a wide dynamic range of vivid colors and rich contrast. Thanks to an expansive 38" (37.5" viewable) frameless screen, ultra-wide 21:9 aspect ratio, and integrated speakers, this monitor is ideal for video editing, content development, and other color-critical applications. With a sleek and modern design, the VP3881 features a future-proof USB type C port as well as DisplayPort technology, and HDMI. What's more, HDCP 2.2 content protection is standard across all ports to provide secure 4K content playback, streaming and gaming. The VP3881 provides an amazing Delta E<2 value precise color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Hardware calibration is also available with the optional ViewSonic Colorbration™ Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, and other professional applications.

Download the ColorPro brochure.

# Specifications

More Information	
UPC	766907916317
Screen Size	38
Viewable Area (in.)	37.52
Panel Type	IPS
Display Resolution	3840 x 1600
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	300 cd/m2
Colors	1.07B
Color Space Support	10bit (8bit+A-FRC)
Aspect Ratio	21:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
Curvature	2300R
PC Resolution (max)	3840 x 1600
Mac® Resolution (max)	3840 x 1600
USB Type A	3
USB Type B	1
USB Type C	1
3.5mm Audio In	1
3.5mm Audio Out	1
HDMI 2.0 (with HDCP 2.2)	2
DisplayPort	1
Internal Speakers	5W (x2)
Amplifier	Class D
Eco Mode (Conserve)	132W
Eco Mode (optimized)	143W
Consumption (typical)	155W
Consumption (max)	170W

Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power [6]
On Screen Display	Main Menu (refer to OSD Table), Short cut key (refer to Short Cuts Function)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~135KHz
Frequency Vertical	24 ~ 75Hz
Digital Sync	Mini-Packet (Display Port 1.4, Type C), TMDS for HDMI 2.0
Height Adjust	130 mm / 5.1 in
Swivel	120º
Tilt (Forward/Back)	1º / 21º
Net (lbs)	28.0
Net Without Stand (lbs)	17.6
Gross (lbs)	43.8
Net (kg)	12.7
Net Without Stand (kg)	8.0
Gross (kg)	19.9
Packaging (in.)	41.2 x 19.3 x 14.8
Physical (in.)	35.3 x 24.8 x 11.8
Physical Without Stand (in.)	35.3 x 15.7 x 4.1
Packaging (mm)	1046.0 x 490.0 x 375.0
Physical (mm)	896.0 x 629.2 x 298.8
Physical Without Stand (mm)	896.0 x 398.0 x 103.1
Regulations	cTUVus, FCC-B, Mexico CoC, EPEAT Certified, Energy Star, Mexico Energy, CB, CE, WEEE, RoHS, ErP, REACH, CU, Ukraine
Package Contents	VP3881 Display, AC/DC Adapter, Power Cable, DisplayPort to DisplayPort, HDMI 2.0 Cable, USB3.1 Gen.1 Type C Cable, USB 3.0 UpStream Cable (Type B to A), Audio Cable (3.5mm audio male to male), Quick Start Guide, ViewSonic Wizard CD-ROM
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued
UPC: 766907916317	







## Contact Sales ViewSonic.com

888.881.8781 email: salesinfo@viewsonic.com