

VX2718-2KPC-MHD-S


## Key Features

### REFURBISHED


- Immersive Curved Screen Design
- 165Hz Refresh Rate
- Ultra-Fast Response Time
- Adaptive-Sync
- Wide Quad HD Resolution




WQHD (2560 X 1440P) RESOLUTION



27  
DISPLAY



MVA  
PANEL



2560 x 1440  
RESOLUTION



## Product Description

With an immersive 1500R curved screen and stunning WQHD 2560 x 1440 resolution, the ViewSonic® VX2718-2KPC-MHD monitor provides an incredible viewing experience for work or play. With features including a high 165Hz\* refresh rate, 1ms (MPRT) response time and adaptive sync technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX2718-2KPC-MHD also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v2.0) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment. \*165Hz refresh rate with DisplayPort

## Specifications

<b>UPC</b>	766907013771
<b>Screen Size</b>	27
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	MVA
<b>Display Resolution</b>	2560 x 1440
<b>Display Resolution</b>	WQHD (2560x1440)
<b>Static Contrast Ratio</b>	4,000:1
<b>Dynamic Contrast Ratio</b>	80,000,000:1
<b>Light Source</b>	LED
<b>Brightness</b>	250 cd/m2
<b>Colors</b>	16.7M
<b>Color Space Support</b>	8 bit (6 bit+FRC)
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	5ms
<b>Response Time (MPRT)</b>	1ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	3,0000
<b>Panel Surface</b>	Anti-Glare type, Hard-coating (3H), Haze 25%
<b>Curvature</b>	1500R
<b>Refresh Rate</b>	165Hz
<b>PC Resolution (max)</b>	2560 x 1440
<b>Mac® Resolution (max)</b>	2560 x 1440
<b>3.5mm Audio Out</b>	1
<b>HDMI 2.0 In</b>	2
<b>DisplayPort</b>	1
<b>Internal Speakers</b>	2W (x2)
<b>Eco Mode (Conserve)</b>	23.5W
<b>Eco Mode (optimized)</b>	27.5W
<b>Consumption (typical)</b>	32.5W
<b>Consumption (max)</b>	40W
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5W
<b>Power Supply</b>	External
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)

<b>On Screen Display</b>	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	75 x 75 mm
<b>Frequency Horizontal</b>	HDMI (v2.0): 30 ~ 222 KHz, DisplayPort (v1.2): 30 ~ 243 KHz
<b>Frequency Vertical</b>	HDMI (v2.0): 48 ~ 144 Hz, DisplayPort (v1.2): 48 ~ 165 Hz
<b>Digital Sync</b>	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.4)
<b>Tilt (Forward/Back)</b>	5° / 20°
<b>Net (lbs)</b>	8.6
<b>Net Without Stand (lbs)</b>	7.3
<b>Gross (lbs)</b>	12.1
<b>Net (kg)</b>	3.9
<b>Net Without Stand (kg)</b>	3.3
<b>Gross (kg)</b>	5.5
<b>Packaging (in.)</b>	27.0 x 17.4 x 6.1
<b>Physical (in.)</b>	24.0 x 18.7 x 8.8
<b>Physical Without Stand (in.)</b>	24.0 x 14.3 x 2.9
<b>Packaging (mm)</b>	687.0 x 443.0 x 156.0
<b>Physical (mm)</b>	611.0 x 475.0 x 225.0
<b>Physical Without Stand (mm)</b>	611.0 x 363.0 x 75.0
<b>Regulations</b>	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
<b>Package Contents</b>	VX2718-2KPC-MHD, Power Cable, AC/DC Adapter, DisplayPort Cable, Quick Start Guide
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
<b>Classification</b>	Refurbished

UPC: 766907013771



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
888.881.8781  
email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)