

LDP163-091 - 163" ALL-IN-ONE PREMIUM 4K ULTRA HD DIRECT VIEW LED DISPLAY

Key Features

- · Seamlessly Immersive
- Versatile Installation Orientation
- Super-Sized Video Walls
- Amazing Visuals
- Theater-Level Audio
- Enhanced Durability and Reliability
- Simple and Easy Setup
- Peace of Mind
- Device Management Made Easy
- Wireless Content Sharing
- Easy Maintenance





163 DISPLAY



Fine Pixel Pitch LED **PANEL**



3840x2160 RESOLUTION

Product **Description**

The ViewSonic® LDP163-091 All-in-One Direct View LED Display is a premium 163" larger-than-life digital screen that delivers an incredible audiovisual experience for any high-end corporate lobby, boardroom or conference room. Featuring a 120% Rec. 709 wide color gamut, lightning-fast 3,840Hz refresh rate, and a peak brightness of 600 nits, this display delivers true-to-life color and extraordinary detail for every video, presentation and lecture. The display is also equipped with Harman Kardon speakers, 4K/HDR/HLG support and PIP/PBP display modes for immersive content delivery. At 25mm slim and lined with a 5mm frameless edge, the sleek LDP163-091 exudes sophistication and elegance in any modern setting.

Specifications

UPC	766907014990
os	Android 9.0
Media Player Type	Yes
СРИ	MTK9669
Memory	4GB DDR4
Storage	64GB (56GB available)
Internal Speakers	20W (x2)
PC Resolution (max)	3840x2160
Mac® Resolution (max)	3840x2160
HDMI 1.4 In	2
HDMI 2.0 In	3
HDMI 2.1 In	1
HDMI 2.0 Out	2
3.5mm Audio Out	1
USB 2.0	3
RS232	1
Ethernet LAN (RJ45)	1
IR in	1
Intel® OPS Slot In (80-pin)	1
Intel® OPS Slot In (80-pin) Voltage	1 100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A)
Voltage	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A)
Voltage Consumption (typical)	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W
Voltage Consumption (typical) Stand-by	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W <0.5W
Voltage Consumption (typical) Stand-by On Screen Display	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W <0.5W Yes
Voltage Consumption (typical) Stand-by On Screen Display Remote Control	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W <0.5W Yes
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W <0.5W Yes 32-104º F (0 - 40º C)
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing)	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W <0.5W Yes 32-104° F (0 - 40° C) 20-80%
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (Ibs)	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) 1860W <0.5W Yes Yes 32-104º F (0 - 40º C) 20-80%
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (lbs) Gross (lbs)	100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 1860W <0.5W Yes Yes 32-104° F (0 - 40° C) 20-80% 494 732
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (lbs) Gross (lbs) Net (kg)	100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 1860W <0.5W Yes Yes 32-104º F (0 - 40º C) 20-80% 494 732
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (lbs) Gross (lbs) Net (kg) Gross (kg)	100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 1860W <0.5W Yes Yes 32-104º F (0 - 40º C) 20-80% 494 732 224 3332
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (lbs) Gross (lbs) Net (kg) Gross (kg) Physical (in.)	100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 1860W <0.5W Yes 32-104º F (0 - 40º C) 20-80% 494 732 224 332 142.1 x 84.5 x 1.4
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (lbs) Gross (lbs) Net (kg) Gross (kg) Physical (in.)	100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 1860W <0.5W Yes Yes 32-104° F (0 - 40° C) 20-80% 494 732 224 332 142.1 x 84.5 x 1.4 142.5 x 84.5 x 3 3610 x 2145.3 x 35
Voltage Consumption (typical) Stand-by On Screen Display Remote Control Temperature Humidity (non-condensing) Net (lbs) Gross (lbs) Net (kg) Gross (kg) Physical (in.) Physical (mm)	100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 1860W <0.5W Yes Yes 32-104° F (0 - 40° C) 20-80% 494 732 224 332 142.1 x 84.5 x 1.4 142.5 x 84.5 x 3 3610 x 2145.3 x 35

Package Contents	Power Cord: x1, LAN Cable (Cat 5A): x1 (5m), IR Extender Cable: x1 (3m), Remote Control: x1, QSG: x1, Wall Mount: x1, Spare Parts: 42, Maintenance Tool: LD-MK-002 x1
Regulations	cTUVus, FCC, RoHS
Wifi	2.4G / 5G n
Display Type	Direct View LED
Screen Size	163
Viewable Area (in.)	163
Orientation	Landscape / Portrait
Light Source	Fine Pixel Pitch LED
LED Pitch Size (mm)	0.93
LED Grayscale	14 bits
Display Resolution	3840 x 2160
Refresh Rate	3,840Hz
Panel Type	Fine Pixel Pitch LED
Aspect Ratio	16:9
Static Contrast Ratio	20,000:1 (Typical)
Backlight Life (Hours)	100,000
Brightness	500 cd/m2
Viewing Angles	170º horizontal, 170º vertical

UPC: 766907014990







Contact Sales
ViewSonic.com
888.881.8781 email:
salesinfo@viewsonic.com