

LS740W - 5,000 ANSI LUMENS WXGA LASER INSTALLATION PROJECTOR

Key Features

- Long-lasting Laser Phosphor Light Source
- Bright Images in Large Spaces
- See the Bigger Picture with a 300" Screen
- Reduced Weight and Size
- Convenient Mounting Flexibility
- Eco-Friendly



Product Description

With the ViewSonic® LS740W laser projector, you can light up every room with brilliant presentations. Featuring the latest laser phosphor technology, the LS740W projector delivers 5,000 ANSI lumens of brightness to ensure crisp images even in rooms with ambient lighting. Enjoy a maintenance-free projection experience without having to deal with complicated lamp replacements. This eco-friendly, high brightness projection solution features a compact design for easier transportation. Experience screen sizes up to 300" in WXGA 1280x800 resolution for show-stopping images designed to fill up boardrooms, lecture halls, auditoriums and other public spaces. The LS740W laser projector comes loaded with features like 1.3x optical zoom, H/V keystone, 4 corner adjustment, 360° projection and portrait mode for easy setup and versatile applications.

Specifications

More Information

UPC	766907022599
Light Source	Laser
Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	5,000 ANSI
Throw Distance	0.77-9.98m (100"@2.54m)
Throw Ratio	1.18-1.54
Keystone	Vertical ($\pm 30^\circ$) / Horizontal ($\pm 30^\circ$)

Lens	1.3x optical zoom
Light Source (watt)	Laser
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07 Billion Colors
Aspect Ratio	16:10
Input Lag	37ms
Frequency Horizontal	15K-102KHz
Frequency Vertical	24-120Hz
PC Resolution (max)	1920 x 1200
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1200
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
Internal Speakers	15W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (max)	210W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Net (lbs)	6.6
Gross (lbs)	10.4
Net (kg)	3.0
Gross (kg)	4.7
Packaging (in.)	15.7 x 11.0 x 6.1
Physical (in.)	11.3 x 8.5 x 5.0
Packaging (mm)	400.0 x 280.0 x 155.0
Physical (mm)	286.0 x 216.0 x 129.0
Regulations	cTUVus
Package Contents	LS740W projector, power cable, remote control, Quick Start Guide

Warranty

Three-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

Notices

*Product and light source lifespan may vary based on actual usage and other factors.
**Express Exchange(R) Service requires product registration. Program, pricing, specifications and availability are subject to change without notice. Copyright(R) 2023.

UPC: 766907022599



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com