



PA504W - 4,000 ANSI LUMENS WXGA EDUCATION & BUSINESS PROJECTOR

Key Features

- Seamless Projector Upgrades
- · Bright in any Environment
- Enhanced Colors
- DLP Technology
- Comprehensive LAN Control









30 - 300 in. / 0.76 - 7.62 m DISPLAY

VGA(640 x 480) to FullHD(1920 x 1080) **RESOLUTION**



Product **Description**

Upgrade your projector setup with the ViewSonic® PA504W high-brightness projector. Featuring a versatile 1.21 – 1.57 throw ratio, this projector can be easily installed onto most existing projector mounts. Plus, with 4,000 ANSI lumens of brightness, audiences can enjoy stunning clarity – even in environments with strong ambient lighting. A Texas instruments .65" DMD chip delivers a high native contrast ratio to make images clearer

and more compelling. Each PA504W projector features a sealed optical engine that reduces maintenance as well as state-of-the-art DLP® technology that enables users to enjoy consistent colors and enhanced clarity over an extended period. Connect your projector to Crestron, AMX, PJ Link, ATEN, Extron or other LAN control systems for streamlined device management. Dual HDMI ports enable users to easily switch between content sources. Add an optional ViewSonic WPD-700 Wireless Screen Casting Kit to the projector's USB-A port to make casting content both faster and cable-free.

Specifications

More Information	
UPC	766907026306
Light Source	DLP Lamp
Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	4,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.5-33.3ft (100"@8.56ft)
Throw Ratio	1.21-1.57
Keystone	Vertical (+/- 40°)
Lens	1.3x optical zoom
Light Source Life, Normal (hours)	5000
Light Source Life, Dynamic Eco-Mode (hours)	15000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	22,000:1
Aspect Ratio	16:10
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120MHz
PC Resolution (max)	VGA(640 x 480) to FullHD(1920 x 1080)
Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
VGA In	1
VGA Out	1
Composite RCA Video In	1
Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	255W
Stand-by	<0.5W
Physical Controls	Keypad, Power key

On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Kensington Lock Slot	1
Net (lbs)	5.14
Gross (lbs)	7.81
Net (kg)	2.33
Gross (kg)	3.54
Packaging (in.)	16.3 x 6.6 x 11.7
Physical (in.)	11.6 x 8.5 x 4.3
Packaging (mm)	415.0 x 168.0 x 297.0
Physical (mm)	294.0 x 218.0 x 110.0
Regulations	cTUVus
Package Contents	PA504W, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907026306







Contact Sales ViewSonic.com 888.881.8781

888.881.8781 email: salesinfo@viewsonic.com