


LS711HD - 4,200 ANSI LUMENS 1080P SHORT THROW LASER INSTALLATION PROJECTOR

Key Features


Bullet list is still needed



35"-300"
DISPLAY



PANEL



GA(640 x 480) to WUXGA_RB(1920 x 1200)*RB-Reduced
Blanking
RESOLUTION



Product Description

From conference rooms to classrooms to indoor driving ranges, the ViewSonic® LS711HD high-brightness projector is designed to light up presentations, lessons and multimedia with incredible brightness and stunning clarity.

Featuring a .49 short throw ratio, this projector can fill a 100" screen from just 3.6 feet away for the ultimate immersive experience.

Enjoy up to 4,200 ANSI lumens of brightness for up to 30,000 hours without ever having to worry about maintenance or finding a replacement bulb. This LS711HD projector uses eco-friendly laser phosphor technology, making it a light-weight, cost-effective projection solution that's easy to transport. A state-of-the-art DMD chip beautifully enhances contrast so that colors pop off the screen. Plus, these durable projectors are built to be run 24/7 without any degradation in quality or overheating.

Get set up faster thanks to convenient features like H/V keystone correction, four corner adjustment, 360° protection capabilities and portrait mode.

Specifications

	More Information
UPC	766907022780
Light Source	Laser
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	4,200 ANSI
Screen Size	35"-300"
Throw Distance	1.2-10.8ft (100"@3.6ft)
Throw Ratio	0.496
Keystone	Vertical (+/- 15°) / Horizontal (+/- 15°)
Lens	Fixed Zoom
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:9
Lens Shift	+15%, -0%(V)
Frequency Horizontal	15K-102KHz
Frequency Vertical	24-120Hz
PC Resolution (max)	GA(640 x 480) to WUXGA_RB(1920 x 1200)*RB-Reduced Blanking
Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
USB 2.0 Type A	1 (5V/1.5A) Power, Service
3.5mm Audio Out	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
Internal Speakers	15W (x1)
Voltage	Input: 100~240V & Output: 19.5VDC / 11.79A
Consumption (typical)	210W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Kensington Lock Slot	1

Net (lbs)	6.95
Gross (lbs)	10.76
Net (kg)	3.15
Gross (kg)	4.88
Packaging (in.)	15.7x11x6.1in
Physical (in.)	11.3x8.5x5 in
Packaging (mm)	400x280x155mm
Physical (mm)	286x216x129mm
Regulations	cTUVus
Package Contents	Projector, power cable, remote control, Quick Start Guide,
Warranty	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907022780



Contact Sales
ViewSonic.com

888.881.8781
 email:
salesinfo@viewsonic.com