


IFP6552-1C-E1 - 65" 4K TOUCH ENABLED VIEWBOARD SMART DISPLAY WITH WIFI ADAPTER AND FIXED WALL MOUNT

Key Features


- ULTRA HD RESOLUTION: 65 Inch 4K Ultra HD (3840x2160p) interactive display
- ADVANCED TOUCH: 33-point multi-touch lets users write on the display with their fingers and stylus pens
- INTEGRATED SOFTWARE: The myViewBoard suite includes Whiteboard, ViewBoard Cast, and more for better engagement
- BETTER SOUND: Built-in beamforming microphone and 45W stereo soundbar delivers optimal sound
- FLEXIBLE CONNECTIVITY: Powerful quad-core processor and versatile connectivity options (HDMI,VGA, RJ45, and USB-C ports)
- EVERYTHING TO GET STARTED: This bundle includes the interactive display, wireless AC adapter and wall mount
- REMOTE MANAGEMENT: Schedule updates and monitor device status with the built-in myViewBoard® Manager software
- PEACE OF MIND: Industry-leading 3-year standard warranty with optional extensions and robust support services



65  
DISPLAY



PANEL



RESOLUTION

Product Description

Ideal for education environments, this all-in-one ViewBoard Bundle includes a 65" ViewBoard IFP6552-1C 4K interactive flat panel, a wireless AC adapter, and a WMK-047-2 wall mount.

Specifications


| More Information    |      |
|---------------------|------|
| Display Type        | LCD  |
| Screen Size         | 65   |
| Viewable Area (in.) | 64.5 |
| Light Source        | LED  |

|                                    |  |
|------------------------------------|--|
| <b>Display Resolution</b>          | 3840 x 2160  |
| <b>Refresh Rate</b>                | 60Hz   |
| <b>Aspect Ratio</b>                | 16:9   |
| <b>Static Contrast Ratio</b>       | 1,200:1  |
| <b>Dynamic Contrast Ratio</b>      | 4,000:1  |
| <b>Backlight Life (Hours)</b>      | 50,000   |
| <b>Brightness</b>                  | 350 cd/m2  |
| <b>Response Time (Typical GTG)</b> | 8ms  |
| <b>Viewing Angles</b>              | 178º horizontal, 178º vertical                               |
| <b>Panel Surface</b>               | Anti-glare 7H tempered glass 3.2mm                           |
| <b>Ethernet LAN</b>                | (10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000) |
| <b>Wifi</b>                        | Optional VB-WIFI-001 adapter, 802.11AX + Bluetooth 5.2       |
| <b>OS</b>                          | ViewBoard OS based on Android 9.0                            |
| <b>GPU</b>                         | ARM Mali-G52   |
| <b>CPU</b>                         | ARM Quad Core A73  |
| <b>CPU Processor Speed</b>         | 1.8GHz   |
| <b>Memory</b>                      | 4GB LPDDR4   |
| <b>Storage</b>                     | 32GB eMMC  |
| <b>Microphone</b>                  | Beamforming array x 8, noise cancelation                     |
| <b>Internal Speakers</b>           | 15W (x2)   |
| <b>Subwoofer</b>                   | 15W (x1)   |
| <b>HDMI 2.0 In</b>                 | 3  |
| <b>VGA</b>                         | 1  |
| <b>SPDIF</b>                       | 1  |
| <b>USB 3.0</b>                     | 2  |
| <b>USB 2.0</b>                     | 3  |
| <b>USB 2.0 Type B</b>              | 2  |
| <b>USB 3.1 Type C</b>              | 1  |
| <b>OPS PC Slot</b>                 | 1  |
| <b>RS232</b>                       | 1  |
| <b>Ethernet LAN (RJ45)</b>         | 1  |
| <b>Intel® OPS Slot In (80-pin)</b> | 1  |
| <b>Voltage</b>                     | 100-240 VAC  |
| <b>Consumption (typical)</b>       | 233.5W   |
| <b>Stand-by</b>                    | <0.5   |
| <b>Temperature</b>                 | 32-104º F (0 - 40º C)  |

|                                  |   |
|----------------------------------|---|
| <b>Humidity (non-condensing)</b> | 10-90%  |
| <b>Touch Technology</b>          | Slim IR   |
| <b>Touch Points</b>              | Windows: 33, Android: 20  |
| <b>Tip Detection</b>             | Dual tips, 2mm and 8mm  |
| <b>Other</b>                     | Palm recognition, object awareness  |
| <b>Latency</b>                   | 4ms   |
| <b>Net (lbs)</b>                 | 93.4  |
| <b>Gross (lbs)</b>               | 114.9   |
| <b>Net (kg)</b>                  | 42.3  |
| <b>Gross (kg)</b>                | 52.0  |
| <b>Packaging (in.)</b>           | 63.7 x 41 x 8.7   |
| <b>Physical (in.)</b>            | 58.6 x 37.3 x 4.7   |
| <b>Packaging (mm)</b>            | 1620.0 x 1043.0 x 220.0   |
| <b>Physical (mm)</b>             | 1488.0 x 948.0 x 120.0  |
| <b>VESA Compatible</b>           | 600 x 400 mm  |
| <b>Screw Size</b>                | M8  |
| <b>Warranty</b>                  | 3-year limited warranty on parts, labor and backlight, onsite warranty  |
| <b>Recycle/Disposal</b>          | Please dispose of in accordance with local, state or federal laws.  |
| <b>Package Contents</b>          | IFP6552-1C display, stylus pen x 2, power cable, HDMI cable, USB cable, AV cable, remote control with batteries, Camera plate, M8 screw x 8, Quick Start Guide. Bundle package includes WiFi Card and WMK-047 |
| <b>Regulations</b>               | cTUVus, FCC, ENERGY STAR, EPEAT Silver, Mexico Energy, CE, CB, RoHS, ErP, WEEE  |

## Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 