

IFP9850 - 98" VIEWBOARD® 4K ULTRA HD INTERACTIVE FLAT PANEL

Key Features

- ULTRA HD RESOLUTION: 98 Inch 4K Ultra HD (3840x2160p) interactive display
- ADVANCED TOUCH: 20-point multi-touch lets users write on the display with their fingers and stylus pens
- INTEGRATED SOFTWARE: The myViewBoard suite includes Whiteboard, ViewBoard Cast, and more for better engagement
- BETTER SOUND: Built-in 32W stereo soundbar delivers optimal sound
- FLEXIBLE CONNECTIVITY: Powerful quad-core processor and versatile connectivity options (HDMI,VGA, RJ45, and USB ports)
- REMOTE MANAGEMENT: Schedule updates and monitor device status with the built-in myViewBoard® Manager software
- PEACE OF MIND: Industry-leading 3-year standard warranty with optional extensions and robust support services









PANEL



RESOLUTION



Product **Description**

Featuring 4K Ultra HD resolution and an advanced, next-generation touchscreen, the ViewSonic® ViewBoard® IFP9850 delivers incredible collaborative capabilities for 21st century boardrooms and classrooms. With integrated myViewBoard® annotation software and ViewBoard Cast streaming software, content creation and sharing has never been easier. What's more, this ENERGY STAR certified display delivers optional slot-in PC capability for more computing-intensive interactive applications. In addition, integrated USB-C provides quick and easy one-wire connectivity. A VESA-compatible design allows for installation on a wall mount, or on an optional trolley cart for more flexible installation in classrooms and meeting rooms.

The downloads listed below are specifically for the IFP9850 **Generation 4**. Looking for downloads for an earlier version? <u>Please click here.</u>

Specifications

More Information	
UPC	766907012880
os	Embedded ViewBoard OS
Media Player Type	Slot-in PC
GPU	Arm Mali-G52 MC2
СРИ	MStsr MT9950, A73*4, 64bit (FW 32bits)
CPU Processor Speed	1.8GHz
Memory	4GB
Storage	32GB
Built-in Software	Android 9
Internal Speakers	16W (x2)
HDMI 2.0 In	3
HDMI Out	1
3.5mm Audio In	1
3.5mm Audio Out	1
SPDIF Audio Out	1
USB 3.0	3
USB 2.0	2
USB Type C	1
Slot-in PC Slot	1
USB B Touch Port	2
RS232	1
Ethernet LAN (RJ45)	1
WIFI Module Slot	1
Intel® OPS Slot In (80-pin)	1
Voltage	100-240 VAC
Consumption (typical)	192.5W
Stand-by	<.5W
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	10-90%
Touch Technology	Slim IR
Touch Points	Windows: 20, Android: 20
Tip Detection	Dual tips, 3mm and 8mm
Net (lbs)	228.4

Gross (lbs)	293.7
Net (kg)	103.6
Gross (kg)	133.2
Packaging (in.)	97.8 x 58.8 x 14.8
Physical (in.)	88.4 x 52.1 x 3.6
Packaging (mm)	2483 x 1493 x 376
Physical (mm)	2245 x 1323 x 91
VESA Compatible	800 x 600 mm
Warranty	3-year limited warranty on parts, labor and backlight, onsite warranty
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Package Contents	10ft power cord, Remote control with AAA battery, 10ft touch USB cable, Stylus x 2, Quick Start Guide + Compliance statement, RS232 adapter, Clamp x 5, Camera Plate, Screw x 8 (camera 2+2, wall mount 4), 10ft HDMI cable, Typc-C cable (data & power)
Regulations	FCC, cTUVus, EPET, ES8, LBL, CE, CB
Ethernet LAN	(10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)
Display Type	LCD
Screen Size	98
Viewable Area (in.)	97.5
Light Source	LED
Display Resolution	3840 x 2160
Aspect Ratio	16:9
Static Contrast Ratio	1,200:1
Backlight Life (Hours)	50,000
Brightness	350 cd/m2
Response Time (Typical GTG)	8ms
Viewing Angles	178º horizontal, 178º vertical
Panel Surface	Anti-glare 7H tempered glass

UPC: 766907012880





Contact Sales ViewSonic.com 888.881.8781

email: salesinfo@viewsonic.com