



# TD2210 - 22" 1080P SINGLE POINT RESISTIVE TOUCH MONITOR WITH USB, DVI AND VGA

## Key Features


- 22 Inch Full HD (1920x1080p) LED touch monitor with 60Hz refresh rate
- Robust single-point resistive touch technology feature a robust, pressure-sensing touchscreen
- 20M:1 MEGA Dynamic Contrast Ratio delivers sharp, crisp images
- MacOS users can access touch and gesture controls on touch displays connected to their Apple devices using ViewSonic's vTouch driver. Not available for iPhone and iPad
- The TD2210 supports laptops, PCs, Macs and POS Systems with USB, DVI-I, and VGA inputs



22  
**DISPLAY**



TN  
**PANEL**



1920 x 1080  
**RESOLUTION**



## Product Description

The TD2210 is a 22" (21.5" viewable) Full HD monitor with resistive touch technology. With a robust, pressure-sensing touchscreen that is resistant to screen contamination, the TD2210 is ideal for use in retail, POS, and commercial environments. Resistive touch technology on the TD2210 is also fully functional in gloved environments and compatible with styluses. Featuring stunning Full HD resolution and 20M:1 MEGA Dynamic Contrast Ratio, the TD2210 delivers extremely sharp and crisp images. Flexible connectivity options include VGA, DVI, and USB ports, and a VESA-mountable design offers additional convenience for use as a wall-mounted display. Industry-leading warranty protection and ViewSonic product quality makes this durable touch display a great long-term investment for a variety of environments.

## Specifications


### More Information

<b>UPC</b>	766907856217
<b>Screen Size</b>	22

<b>Viewable Area (in.)</b>	21.5
<b>Display Resolution</b>	1920 x 1080
<b>Static Contrast Ratio</b>	1,000:1
<b>Dynamic Contrast Ratio</b>	20M:1
<b>Brightness</b>	250 cd/m2
<b>Backlight Life (Hours)</b>	40,000
<b>Response Time (Typical GTG)</b>	5ms
<b>Panel Type</b>	TN
<b>Colors</b>	16.7M
<b>Viewing Angles</b>	170° horizontal, 160° vertical
<b>Light Source</b>	LED
<b>Panel Surface</b>	3H Scratch Resistant Surface Hardness
<b>Aspect Ratio</b>	16:9
<b>PC Resolution (max)</b>	1920 x 1080
<b>Touch Technology</b>	Resistive
<b>Touch Points</b>	1-Point Touch
<b>USB Type A</b>	1
<b>USB Type B</b>	1
<b>VGA</b>	1
<b>DVI-I</b>	1
<b>Internal Speakers</b>	2W (x2)
<b>Frequency Horizontal</b>	24 ~ 83KHz
<b>Frequency Vertical</b>	50 ~ 76Hz
<b>Analog Sync</b>	Separate Sync / Composite Sync / Sync on Green
<b>Eco Mode (Conserve)</b>	11.5W
<b>Eco Mode (optimized)</b>	14W
<b>Consumption (typical)</b>	17.5W
<b>Consumption (max)</b>	29.5W
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5W
<b>Physical Controls</b>	GameMode, 1, 2, 3, 4, Power
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>Tilt (Forward/Back)</b>	5° / 20°

<b>Kensington Lock Slot</b>	1
<b>VESA Compatible</b>	100 x 100 mm
<b>Gross (kg)</b>	6.5
<b>Net (kg)</b>	4.8
<b>Net Without Stand (kg)</b>	3.9
<b>Net (lbs)</b>	10.5
<b>Net Without Stand (lbs)</b>	8.7
<b>Gross (lbs)</b>	14.4
<b>Packaging (mm)</b>	570 x 427 x 214
<b>Physical (mm)</b>	512 x 364 x 240
<b>Physical Without Stand (mm)</b>	512 x 311 x 64
<b>Packaging (in.)</b>	22.4 x 16.8 x 8.4
<b>Physical (in.)</b>	20.1 x 14.3 x 9.5
<b>Physical Without Stand (in.)</b>	20.1 x 12.2 x 2.5
<b>Regulations</b>	cULus, FCC-B, ICES003, Energy Star, EPEAT, UL-MX-CoC, Mexico Energy
<b>Package Contents</b>	LCD Display, Power Cable, VGA Cable, DVI Cable, USB2.0 Cable, Audio Cable, Quick Start Guide, ViewSonic Wizard CD-ROM
<b>Warranty</b>	Three-year limited warranty on parts, labor and backlight
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.

UPC: 766907856217



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)