

## LDM216-251 - 216" ALL-IN-ONE MAINSTREAM FULL HD DIRECT VIEW LED DISPLAY

### Key Features

---


- High-Impact Messaging
- Simple and Easy Setup
- Amazing Audio-Visual Experience
- Device Management Made Easy
- Easy Maintenance



216  
DISPLAY



PANEL



1920x1080  
RESOLUTION



### Product Description

---

The ViewSonic® LDM216-251 is an innovative All-in-One Direct View LED display. With a huge 216" screen size, the LDM216-251 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 2.5mm fine pixel pitch, 600-nit high brightness, 3,840Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut. What's more, its ultra-slim 35mm thickness and bezel-free design delivers sleek looks whether its hanging on a wall or mounted on an optional aluminum floor stand. Despite its huge screen size, a front-assembly modular design enables easy delivery, installation, and maintenance. And with remote configuration and content management system support, the ViewSonic LDM216-251 is also suitable for a wide array of diverse signage applications.

### Specifications

---

<b>UPC</b>	766907014488
<b>OS</b>	Android 8.0
<b>CPU</b>	Hi3751 V811
<b>Memory</b>	4GB DDR4
<b>Storage</b>	32GB (26GB available)
<b>Internal Speakers</b>	5W (x2)
<b>PC Resolution (max)</b>	1920x1080
<b>Mac® Resolution (max)</b>	1920x1080
<b>HDMI 1.4 (with HDCP 1.4)</b>	2
<b>HDMI 1.4 Out (with HDCP 1.4)</b>	1
<b>3.5mm Audio Out</b>	1
<b>USB 3.0</b>	1
<b>USB 2.0</b>	2
<b>USB 2.0 Type B</b>	1
<b>RS232</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>IR in</b>	1
<b>Intel® OPS Slot In (80-pin)</b>	1
<b>Voltage</b>	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A)
<b>Consumption (max)</b>	4900W
<b>Consumption (typical)</b>	3430W
<b>Stand-by</b>	<0.5W
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-80%
<b>Net (lbs)</b>	750
<b>Gross (lbs)</b>	992
<b>Net (kg)</b>	340
<b>Gross (kg)</b>	450
<b>Packaging (in.)</b>	109.4 x 33.5 x 40.2
<b>Physical (in.)</b>	189.8 x 110.9 x 1.4
<b>Physical with Wall Mount (in.)</b>	189.8 x 110.9 x 2.2
<b>Packaging (mm)</b>	2780.0 x 850.0 x 1020.0
<b>Physical (mm)</b>	4820.95 x 2818.45 x 35.0
<b>Physical with Wall Mount (mm)</b>	4820.95 x 2818.45 x 56.0
<b>Warranty</b>	Three (3) years from the date of first consumer purchase for parts and labor.
<b>Display Type</b>	Direct View LED

<b>Screen Size</b>	216
<b>Viewable Area (in.)</b>	216
<b>Orientation</b>	Landscape
<b>Light Source</b>	Fine Pixel Pitch LED
<b>LED Pitch Size (mm)</b>	2.5
<b>LED Grayscale</b>	14 bits
<b>Display Resolution</b>	1920 x 1080
<b>Refresh Rate</b>	3,840Hz
<b>Aspect Ratio</b>	16:9
<b>Static Contrast Ratio</b>	6,000:1
<b>Backlight Life (Hours)</b>	100,000
<b>Brightness</b>	600-nit
<b>Viewing Angles</b>	160° horizontal, 160° vertical

UPC: 766907014488



**Contact Sales**

[ViewSonic.com](http://ViewSonic.com)

888.881.8781 ☎

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)