

VA2714-H - 27" 1080P IPS MONITOR WITH HDMI, VGA

Key Features


- Wide-angle viewing with SuperClear® IPS technology
- Three-sided frameless design
- · HDMI and VGA connectivity
- Variable refresh rate technologies deliver smoother images
- Full HD 1080p resolution







PANEL



1920 x 1080 **RESOLUTION**



Product **Description**

Experience flexible connectivity, wide-angle viewing, and stunning screen performance with the 27"" ViewSonic® VA2714-H monitor. This three-sided frameless display features state-of-the-art IPS panel technology which enables users to enjoy powerful brightness and impressive contrast from nearly any viewing angle. The VA2714-H includes a VGA port, an HDMI port, and an HDMI cable, ensuring flexible connectivity to PCs, laptops, and gaming consoles. Enjoy a smoother viewing experience with built-in variable refresh rate technology that virtually eliminates screen tearing and stuttering. Upgrade the way you work and play with the ViewSonic VA2714-H monitor today.

Specifications

More Information

Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	300 cd/m2
Colors	16.7M
Color Space Support	6 bit + FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	4ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Eco Mode (Conserve)	15W
Eco Mode (optimized)	17W
Consumption (typical)	19W
Consumption (max)	28W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm

	HDMI 1.4: 24 ~ 115 KHz; RGB Analog: 24 ~ 86 KHz
Frequency Vertical	HDMI 1.4: 48 ~100 Hz; RGB Analog: 48 ~75 Hz
Tilt (Forward/Back) 5	5º / 20º
Net (lbs)	10.6
Net Without Stand (lbs) 9	9.0
Gross (lbs)	14.1
Net (kg) 4	4.8
Net Without Stand (kg) 4	4.1
Gross (kg) 6	6.4
Packaging (in.) 2	26.8 x 17.5 x 5.6
Physical (in.)	24.1 x 17.1x 9.5
Physical Without Stand (in.) 2	24.1 x 14.3 x 1.9
Packaging (mm) 6	680.0 x 445.0 x 143.0
Physical (mm) 6	611.9 x 434.6 x 242.2
Physical Without Stand (mm) 6	611.9 x 364.2 x 49.1
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy, RoHS, WEEE
Package Contents	VA2714-H Display, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907029055







Contact Sales
ViewSonic.com
888.881.8781 email:
salesinfo@viewsonic.com