


PX747-4K - BRIGHT 3500 LUMENS 4K HOME THEATER PROJECTOR WITH HDR SUPPORT

Key Features


- Stunning 4K Ultra HD Resolution
- HDR Content Support
- 3,500 lumen brightness
- Dual HDMI Connectivity
- Long Lamp Life



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



3840 x 2160
RESOLUTION



Product Description

4K all day. With incredible Ultra HD resolution and a high brightness of 3,500 lumens, the ViewSonic® PX747-4K projector delivers stunning home entertainment around the clock: day or night, in bright rooms or dark. Featuring HDR compatibility, exclusive SuperColor™ technology, and true Ultra HD 3840 x 2160 resolution, the PX747-4K delivers a breathtaking home cinema experience you expect to only get at the movie theater. With high brightness and room-filling sound, this projector provides bright visuals and immersive audio in nearly any room or environment. What's more, an energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours*. Set-up is a breeze too: 1.2x optical zoom and versatile connectivity options allow for more flexible mounting and easy installation. For an amazing home theater viewing experience with lifelike color and razor-sharp details, the PX747-4K delivers.

*Lamp life may vary based on actual usage and other factors.

Specifications

	More Information
UPC	766907961416
Light Source	DLP Lamp
Display Resolution	4K (3840x2160)
Display Resolution	3840 x 2160
Brightness (Lumens)	3,500 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	3.2 - 38.4 ft / 1.0 - 11.7 m
Throw Ratio	1.47 - 1.76
Keystone	Vertical (+/- 40°)
Lens	1.2x optical zoom
Light Source (watt)	240
Light Source Life, Normal (hours)	4000
Light Source Life, Dynamic Eco-Mode (hours)	15000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	12,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~135KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	3840 x 2160
PC Resolution (min)	640 x 480
Mac® Resolution (max)	3840 x 2160
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	1
HDMI 2.0 (with HDCP 2.2)	1
VGA In	1
Mini USB	1
Internal Speakers	10W (x1)

Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	310W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	9.3
Gross (lbs)	11.0
Net (kg)	4.2
Gross (kg)	5.0
Packaging (in.)	16.4 x 8.2 x 13.2
Physical (in.)	13.1 x 5.3 x 10.3
Packaging (mm)	417.0 x 207.0 x 336.0
Physical (mm)	332.0 x 135.0 x 261.0
Regulations	FCC, cTUVus, ROHS
Package Contents	PX747-4K projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907961416



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com