



LS860WU - 5000 LUMENS WUXGA SHORT THROW LASER PROJECTOR WITH 1.3X OPTICAL ZOOM

Key Features


- Bright Images in Large Spaces
- Long-Lasting Laser Phosphor Light Source
- One-Wire HDBT® Input
- 360-Degree Orientation
- Portrait Mode Presentation
- Short Throw
- Software Updates Via Mini USB



60 - 200 in. / 1.5 - 5.1 m
DISPLAY



PANEL



1920 x 1200
RESOLUTION



Product Description

Bright and versatile for any professional installation, the ViewSonic® LS860WU WUXGA laser projector delivers everything you need for big screens in big venues. Delivering 5,000 lumens of advanced high brightness, 300,000:1 contrast ratio, and up to 20,000 hours* of light source life, this projector is ideal for auditoriums, lecture halls, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. This top-notch performer is also easy to deploy and manage with its vertical/horizontal keystone, 4-corner adjustment, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. A short throw lens with a 0.8 throw ratio offers large projection images for smaller rooms. Thanks to the built-in HDBT receiver, the projector is capable of receiving uncompressed HD video and audio from over 200 feet away via network cable. Moreover, 360-degree tilt angle projection, portrait mode, and 24/7 operation allow for extreme mounting flexibility. The ViewSonic® LS860WU is the ideal WUXGA laser projector for professional installations, large venues, and business and education environments. *Light source life may vary based on actual usage and other factors.

Specifications

| | More Information |
|----------------------------------------------------|-------------------------------------------|
| UPC | 766907003987 |
| Light Source | DLP Laser |
| Display Resolution | WUXGA (1920x1200) |
| Display Resolution | 1920 x 1200 |
| Brightness (Lumens) | 5,000 ANSI |
| Screen Size | 60 - 200 in. / 1.5 - 5.1 m |
| Throw Distance | 3.4 - 12.6 ft / 1.0 - 3.8 m |
| Throw Ratio | 0.81-0.89 |
| Keystone | Vertical (+/- 40°) / Horizontal (+/- 40°) |
| Lens | 1.1x optical zoom |
| Light Source (watt) | Nichia 67W X 2 |
| Light Source Life, Normal (hours) | 20000 |
| Light Source Life, Dynamic Eco-Mode (hours) | 20000 |
| Color Depth | 1.07 Billion Colors |
| Dynamic Contrast Ratio | 30,000,000:1 |
| Aspect Ratio | 16:10 |
| Input Lag | 37ms |
| Lens Shift | Verical: +/- 50%, Horizontal: +/- 23% |
| Operation Rating | 24/7 |
| Frequency Horizontal | 15K-102KHz |
| Frequency Vertical | 23-120Hz |
| PC Resolution (max) | 1920 x 1200 |
| PC Resolution (min) | 640 x 480 |
| Mac® Resolution (max) | 1920 x 1200 |
| Mac® Resolution (min) | 640 x 480 |
| USB 2.0 Type A | 1 |
| Ethernet LAN (RJ45) | 1 |
| 3.5mm 12V Trigger | 1 |
| 3.5mm Audio Out | 1 |
| 3.5mm Audio In | 1 |
| Control (RS232) | 1 |
| HDMI 1.4 (with HDCP 1.4) | 2 |
| VGA In | 1 |

| | |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| VGA Out | 1 |
| Composite RCA Video In | 1 |
| S-Video In | 1 |
| RCA Audio In (L/R) | 1 |
| 3D VESA | 1 |
| HDBT | 1 |
| Internal Speakers | 10W (x2) |
| Stand-by | <0.5W |
| On Screen Display | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |
| Temperature | 32-104° F (0 - 40° C) |
| Humidity (non-condensing) | 0-90% |
| Kensington Lock Slot | 1 |
| Net (lbs) | 14.6 |
| Gross (lbs) | 20.1 |
| Net (kg) | 6.6 |
| Gross (kg) | 9.1 |
| Packaging (in.) | 20.3 x 19.3 x 10.9 |
| Physical (in.) | 15.9 x 12.0 x 5.7 |
| Packaging (mm) | 515.0 x 490.0 x 276.0 |
| Physical (mm) | 405.0 x 305.0 x 145.0 |
| Regulations | FCC, cTUVus, ROHS |
| Package Contents | LS860WU projector, power cable, VGA cable, remote control, Quick Start Guide |
| Warranty | Five-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |

UPC: 766907003987



Projection Distance and Size
Where to place your projector to get the screen size you want.



Projection Distance (ft.)
*Based on throw ratio of 0.81-0.89
**Can project up to 508in | 200in.

5000 LUMENS and WUXGA RESOLUTION



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com