




PG707X - 4000 LUMENS XGA NETWORKABLE PROJECTOR WITH 1.3X OPTICAL ZOOM AND LOW INPUT LAG

Key Features


- High brightness 4000 Lumens XGA projector with advanced visual features
- 1.3x optical zoom lens, H/V keystone and corner adjustment for flexible setup
- SuperEco Mode allows the lamp to shine bright for up to 20,000 hours
- 6 segment color wheel and dynamic lamp control capabilities provide vivid colors
- A low 16ms input latency provides faster frame-by-frame action for smooth images without delay
- Supports most media players, PCs, Macs, and mobile devices with inputs such as Dual HDMI, USB, Ethernet LAN



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION

Flexible connectivity for your favorite devices.



1.3x Optical Zoom

20,000 hours Lamp Life
(Eco Mode)



x2 HDMI 1.4 (HDCP 1.4)
x2 VGA (In/Out)
x1 USB 2.0 Type A
x1 Ethernet Lan (RJ45)
x2 3.5mm Audio In/Out
x1 RS232 In
x1 Composite RCA Video In
x1 Kensington Lock Slot

Product Description

The ViewSonic® PG707X projector features 4,000 lumens, XGA 1024x768 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. A 10W speaker delivers incredibly clear and audible sound, while a top lamp door enables easy access for lamp maintenance. The PG707X is the ideal high brightness projector for use in both classroom and corporate settings.

Specifications

[More Information](#)

UPC	766907006193
Light Source	DLP Lamp
Display Resolution	XGA (1024x768)
Display Resolution	1024 x 768
Brightness (Lumens)	4,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	3.0 - 39.4 ft / .9 - 12.0 m
Throw Ratio	1.51-1.97
Keystone	Vertical (+/- 40º) / Horizontal (+/- 40º)
Lens	1.3x optical zoom
Light Source (watt)	203
Light Source Life, Normal (hours)	6000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	22,000:1
Aspect Ratio	4:3
Input Lag	37ms
Frequency Horizontal	15K~105KHz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
VGA In	1
VGA Out	1
Composite RCA Video In	1
Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	280W
Stand-by	<0.5W
Physical Controls	Keypad, Power key

On Screen Display

Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Temperature

32-104° F (0 - 40° C)

Kensington Lock Slot

1

Net (lbs)

5.3

Gross (lbs)

7.5

Net (kg)

2.4

Gross (kg)

3.6

Packaging (in.)

16.3 x 6.6 x 11.7

Physical (in.)

11.6 x 8.6 x 4.3

Packaging (mm)

415.0 x 168.0 x 297.0

Physical (mm)

294.0 x 218.0 x 110.0

Regulations

cTUVus

Package Contents

PG707X projector, power cable, VGA cable, remote control, Quick Start Guide,

Warranty

Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).


Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

UPC: 766907006193

**Projection Distance and Size**

Where to place your projector to get the screen size you want.



Projection Distance (ft.)

*Based on throw ratio of 1.31-1.97

**Can project up to 76 m | 300 in.

4000 LUMENS and XGA (1024x768) RESOLUTION

**Contact Sales**

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com