

VB-CAM-201 - 4K WIDE-ANGLE CONFERENCE CAMERA WITH PAN/TILT/ZOOM, MICROPHONE ARRAY, AND BLUETOOTH

Key Features

- Better Conference Calls
- Wide-Angle Advanced Optic Lens
- Clear Audio and Communication
- Software Versatility
- Expandable Bluetooth
 Connectivity
- Easy and Flexible Installation



Product **Description**

The ViewSonic[®] VB-CAM-201 is a 4K video conferencing camera perfect for medium to large-sized conference rooms and boardrooms. With 4K Ultra HD resolution and a 120° super wide-angle lens, the VB-CAM-201 captures everyone in a meeting room with stunning clarity. Voice-tracking technology, combined with 5x digital zoom, ensures that the speaker is always on camera. In addition, an 8W speaker and a four-microphone array with noise and echo cancellation technologies ensure that everyone on your call feels as if they are in the room with you. Plug-and-play connectivity with ViewSonic ViewBoard® interactive displays and commercial displays make setup quick and easy.

Specifications

More Information		
Sensor	1/2.5 inch, CMOS, 8.51M pixel	
Lens	5x digital zoom, pan/tilt ±15°	
Digital Noise Reduction	2D, 3D digital noise reduction	
White Balance	Auotmatic, Indoor, Outdoor, One Push, Manual	
Field of View (FOV)	120°(DFOV), 110°(HFOV)	
Display Resolution	3840 × 2160	
PTZ	MPT + EPTZ	

USS 2.0 Type 1IUSS 3.0 Type 2IUSS 3.0 Type 4IUSS 3.0 Type 4	HDMI 2.0 Out	1
Ethernet LAN (R)45)1Fithernet LAN (R)45)44(330%5, 1080P@60fps, 720P@60fps, 720P@30fps, etc.Video SupporH264/ M/PEG /VU/2 /VV12CompressionH264/ M/PEG /VU/2 /VV12SensitVity966B at 0.5m / 1.6 ftSensitVity32X sampling rate, high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto NoiseSuppression / Auto Sain controlSuppression / Auto Sain controlMicrophoneBeamforming microphoneMicrophone array4 microphoneBistance6// 2.0 ftMinimum Hardware Speek(P) (Recommended) 2.4 GHz Intel" Core 2 ^m Duo processor or higher, RAM (Recommedined) 2GB of Memory or Figher, USB 2.0 Type-A required for 1080p video output, USB Type-C required for 4K UHD video outputVoltage0C 12V/1 SA AdapterConsumption (typical)18WBluetooth 5.018WBluetooth 5.0190%Packaging (in.)23.62 x 5.31 x 4.53Packaging (in.)23.62 x 5.31 x 4.53Packaging (in.)23.62 x 5.31 x 4.53Packaging (in.)28.66Gross (ib)4.86Gross (ib)4.86Gross (ib)4.86Gross (ib)4.86Winded warranty on parts and laborRecycled/DisposedPiese dispose of microphone at al accordance with local, state or federal laws.Recycled/DisposedFiese dispose of microphone at al alborMiritory (ib)4.86Gross (ib)%C-C (Ci, (Ci, (Ci, (Ci, (Ci, U, U)Miritory (ic)Piese dispose of microphone at al laborBuetoothF	USB 2.0 Type A	1
Video Suppor4<@30/up. 1080P@60/up. 120P@60/up. 720P@30/up. etc.	USB 3.0 Type C	1
AudioH264/ MJPEG / MUY2 / MV12Internal Speakers8W (x1)Sensitivity9688 at 0.5m / 1.6 ftAudio features32X sampling rate, high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto NoiseJUSB protocolSupport UAC 2.0MicrophoneBeamforming microphoneMicrophone arrow4 microphoneDistance6m / 20 ftDistanceECH / Recommended) 2.4GHz Intel® Core 2 ^m Duo processor or higher, RAM (Recommended) 2EB oft Memory or higher, USB 2.0 Typoe-Required for 1080 privideo output, USB Type-C required for 4UDD video output, USB Type-C video output, USB Type-C video output, USB Type-C video output, USB Type-C video output, USB Type-C video output, USB Type-C video output, USB Type-C video output, USB Type-C video	Ethernet LAN (RJ45)	1
Internal Speakers80(4)9680 to.Sm /1.6 ftAudo features327, Sampling rate, high-definition broadband audo, full-duplex voice / Auto Echo cancellation / Auto Noise9680 to.Sm /U.C.2.0MicrophoneMicrophone1010 to.S.0Microphone arrow6012 to.S.0Microphone0120 to.S.0Minamu Hardwares Degi0120 to.S.01010 to.S.0	Video Support	4K@30fps, 1080P@60fps, 1080P@30fps, 720P@60fps, 720P@30fps, etc.
Sensitivity96dB at 0.5m / 1.6 ftAudio features32X sampling rate. high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto Noise suppression / Auto Gain controlUSB protocolSupport UAC 2.0Beamforming microphoneBeamforming microphoneMicrophone array4 microphoneMicrophone arrayCPU (Recommended) 2.4 fdE2 Intel [®] Core 2. ^{se} Duo processor or higher, RAM (Recommended) 2.6B of Memory or higher, DE2 2.0 Type-A required for 1000p video output, USB Type-C required for 4K UHD video outputMinimum Hardware SpeesCPU (Recommended) 2.4 fdE2 Intel [®] Core 2. ^{se} Duo processor or higher, RAM (Recommended) 2.6B of Memory or higher, DE2 2.0 Type-A required for 1000p video output, USB Type-C required for 4K UHD video outputMinimum Hardware SpeesDe1 2UV1.5A AdapterBuetoothBuetooth 5.0BuetoothBuetooth 5.0BuetoothSolo Core 2.5B of Core 2.5B	Compression	H.264 / MJPEG /YUY2 /NV12
Audio features 32K sampling rate, high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto Noise suppression / Auto Gain control USB protocol Support UAC 2.0 Microphone Beamforming microphone Microphone array 4 microphone Microphone array 4 microphone Distance 6m / 20 ft Minimum Hardware Spees CPU (Recommended) 2.4GHz Intel [®] Core 2 ^{ore} Duo processor or higher, RAM (Recommedned) 2GB of Memory or higher, USB 2.0 Type-A required for 1080p video output. USB Type-C required for 4K UHD video output Voltage Dc 12V/1.SA Adapter Donumption (typica) Bluetooth 5.0 Bluetooth Bluetooth 5.0 2104 F (0 - 40° C) N/A Packaging (in.) 26.54 × 18.98 × 18.66 Physical (in.) 23.62 × 5.31 × 4.53 Microphone 600 × 135 × 115 Microphone 4.86 Gross (lbs) 28.66 Gross (lbs) Ale6 Warranty One-year limited warranty on parts and labor Meacyle/Disposal Please dispose of in accordance with local, state or federal laws. Recycle/Disposal Pleacked Spose of in accordance with local, state or fede	Internal Speakers	8W (x1)
Auto reaturessuppression 7 Auto Gain controlUSB protocolSupport UAC 2.0MicrophoneBeamforming microphoneMicrophone array4 microphones0Microphone array6 m/ 20 ftDistanceCPU (Recommended) 2.4GHz Intel [®] Core 2. ^m Duo processor or higher, RAM (Recommended) 2.GB of Memory or higher, USB 2.0 Type-A required for 1080p video output, USB Type-C required for 4K UHD video outputVoltageDC 12V/1.SA AdapterBluetooth16WBluetooth 5.018WBluetooth 5.02.049* F (0 - 40° C)Humidity (non-condensity)0.90%Vireless ConnectivityN/AAdagter2.654 × 18.98 × 18.66Physical (in.)2.652 × 13.8.4.53Ackaging (in.)6.74 × 482 × 4746.00 × 135 × 1156.66Maranty4.86Arranty0.90Ackaging (in.)8.66Ackaging (in.)4.86Ackaging (in.)6.74 × 482 × 474Ackaging (in.)6.76 × 2.61Ackaging (in.)8.66Ackaging (in.)8.66Ackaging (in.)9.66Ackaging (in.)9.66Ackaging (in.)8.66Ackaging (in.)9.66Ackaging (in.)9.66Ackaging (in.)9.66Ackaging (in.)9.66Ackaging (in.)6.76Ackaging (in.)6.76Ackaging (in.)6.76Ackaging (in.)7.67Ackaging (in.)7.67Ackaging (in.)7.67Ackaging (in.	Sensitivity	96dB at 0.5m / 1.6 ft
Microphone Beamforming microphone Microphone array 4 microphones Microphone array 4 microphones Distance 6m / 20 ft Minimum Hardware Speez CPU (Recommended) 2.4GHz Intel® Core 2™ Duo processor or higher, RAM (Recommedned) 2GB of Memory or higher, USB 2.0 Type-A required for 1800 video output, USB Type-C required for 4K UHD video output Voltage DC 12/1.5A Adapter Consumption (typical Bluetooth 5.0 Bluetooth Bluetool 5.0 Humidity (non-condensing) Col 40° C) Vireless Connectivity V/A Packaging (nn) 6.54 x 18.98 x 18.66 Physical (in.) 2.652 x 5.31 x 4.53 Ot 2.35 x 115 Consult Microphone Gov 3.35 x 115 Packaging (mm) 6.04 x 135 x 115 Microphone Recycle/Disposal Res dispose of in accordance with local, state or federal laws. Recycle/Disposal Pics-CM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wait Antor x 5	Audio features	
Microphone array 4 microphones Distance 6m / 20 ft Minimum Hardware Spee; CPU (Recommended) 2.4GHz Intel [®] Core 2 [™] Duo processor or higher, RAM (Recommedned) 2GB of Memory or higher, USB 2.0 Type-A required for 1080 proteo output, USB Type-C required for 4K UHD video output Voltage DC 12V/1.5A Adapter Bluetooth Bluetooth 5.0 Bluetooth Bluetooth 5.0 Temperature 32-104° F (0 - 40° C) Vireless Connectivity N/A Packaging (in.) 26.54 × 18.98 × 18.66 Physical (in.) 23.62 × 5.31 × 4.53 Packaging (im.) 674 × 482 × 474 600 × 135 × 115 600 × 135 × 115 Microphones 28.66 Gross (lbs) 28.66 Warranty One-year limited warranty on parts and labor Marranty Pease dispose of in accordance with local, state or federal laws. FCC, FCC ID, CE, IC ID, LVD VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wail Anchorx x 6	USB protocol	Support UAC 2.0
Distance6n/20 ftMinimum HardwarespecCPU (Recommended) 2.4GHz Intel [®] Core 2 [™] Duo processor or higher, RAM (Recommended) 2.GB of Memory or higher, UBB 2.0 strype-A required for 1080 proteos output, USB Type-C required for AK UHD video outputVotageDi 22/J.5A AdapterConsumption (yild)IsolandBluetoothIsolandBluetoothIsolandBluetoothIsolandOr 200StanceMinimum HardwarespecNaBluetoothIsoland <th>Microphone</th> <th>Beamforming microphone</th>	Microphone	Beamforming microphone
Minimum Hardware Spec CPU (Recommended) 2.4GHz Intel [®] Core 2 [™] Duo processor or higher, RAM (Recommedned) 2GB of Memory or higher, USB 2.0 Type-A required for 1080p video output, USB Type-C required for 4K UHD video output Voltage Dc 122V/1.5A Adapter Bluetooth Bluetooth 5.0 Bluetooth Bluetooth 5.0 Voltage De 090% Wireless Connectivity N/A Packaging (in.) 26.54 x 18.98 x 18.66 Gross (ib.) 26.54 x 18.98 x 18.66 Packaging (in.) 26.54 x 18.98 x 18.66 Bitter (is.) 26.54 x 18.98 x 18.76 Bitter (is.)	Microphone array	4 microphones
Number Application Notage DC 12V/1.5A Adapter DC 12V/1.5A Adapter 18W Bluetooth Bluetooth 5.0 Bluetooth Bluetooth 5.0 Temperature 32-104º F (0 - 40º C) Humidity (non-condensing) 20-90% Victage N/A Packaging (in.) 23.62 × 5.31 × 4.53 Additional Science Control 600 × 135 × 115 Physical (mm) 600 × 135 × 115 Additional Science Control 8.86 Marranty One-year limited warranty on parts and labor Net cycle/Disposal Please dispose of in accordance with local, state or federal laws. FCC, FCC ID, CE, IC ID, LVD Be-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Science X of Warranty	Distance	6m / 20 ft
Consumption (typical)18WBluetoothBluetooth 5.0Bluetooth32-104° F (0 - 40° C)Temperature32-104° F (0 - 40° C)Wireless ConnectivityN/APackaging (in.)20-90%Packaging (in.)20.52 × 3.31 × 4.53Physical (in.)20.52 × 3.31 × 4.53Physical (in.)600 × 1.35 × 1.15Physical (mm)600 × 1.35 × 1.15Other Statistics8.66Other Statistics9.66Other Statistics9.66Other Statistics9.66Other Statistics9.66Recycle/DisposalFease dispose of in accordance with local, state or federal laws.PAckAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Brack to Scatistics	Minimum Hardware Specs	
Bluetooth Bluetooth 5.0 Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-90% Wireless Connectivity N/A Packaging (in.) 26.54 × 18.98 × 18.66 Physical (in.) 23.62 × 5.31 × 4.53 Packaging (mm) 674 × 482 × 474 600 × 135 × 115 600 × 135 × 115 Physical (mm) 600 × 135 × 115 Gross (lbs) 28.66 Gross (lbs) 28.66 Verranty One-year limited warranty on parts and labor Please dispose of in accordance with local, state or federal laws. Recycle/Disposal FCC, FCC ID, CE, IC ID, LVD PACKAGE CONTENTS Warranty. De-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Voltage	DC 12V/1.5A Adapter
Temperature32-104º F (0 - 40º C)Humidity (non-condensing)20-90%Wireless ConnectivityN/APackaging (in.)26.54 × 18.98 × 18.66Physical (in.)23.62 × 5.31 × 4.53Physical (in.)674 × 482 × 474600 × 135 × 115600 × 135 × 115Net (lbs)4.86Gross (lbs)28.66Gross (lbs)28.66WarrantyOne-year limited warranty on parts and laborPlease dispose of in accordance with local, state or federal laws.RegulationsFC, FCC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, wall Anchor x 6	Consumption (typical)	18W
Humidity (non-condensing)20-90%Wireless ConnectivityN/APackaging (in.)26.54 × 18.98 × 18.66Physical (in.)23.62 × 5.31 × 4.53Physical (in.)674 × 482 × 474600 × 135 × 115600 × 135 × 115Net (lbs)4.86Gross (lbs)28.66WarrantyOne-year limited warranty on parts and laborNarrantyPlease dispose of in accordance with local, state or federal laws.RegulationsFCC, FCC ID, CE, IC ID, IVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Bluetooth	Bluetooth 5.0
Wireless ConnectivityN/APackaging (in.)26.54 × 18.98 × 18.66Physical (in.)23.62 × 5.31 × 4.53Packaging (mm)674 × 482 × 474600 × 135 × 115600 × 135 × 115Net (lbs)4.86Gross (lbs)28.66Gross (lbs)28.66WarrantyOne-year limited warranty on parts and laborPeckage dispose of in accordance with local, state or federal laws.FCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Temperature	32-104º F (0 - 40º C)
Packaging (in.)26.54 × 18.98 × 18.66Physical (in.)23.62 × 5.31 × 4.53Packaging (mm)674 × 482 × 474600 × 135 × 115600 × 135 × 115Net (lbs)4.86Gross (lbs)28.66WarrantyOne-year limited warranty on parts and laborNet quationsPlease dispose of in accordance with local, state or federal laws.RegulationsFCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSWB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Humidity (non-condensing)	20-90%
Physical (in.)23.62 x 5.31 x 4.53Packaging (mm)674 x 482 x 474600 x 135 x 115600 x 135 x 115Net (lbs)4.86Gross (lbs)28.66Gross (kg)4.86WarrantyOne-year limited warranty on parts and laborNet (lbs)Please dispose of in accordance with local, state or federal laws.FCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Wireless Connectivity	N/A
Packaging (mm)674 × 482 × 474Physical (mm)600 × 135 × 115600 × 135 × 1154.86Ret (lbs)4.8628.6628.66Gross (kg)4.86WarrantyOne-year limited warranty on parts and laborPlease dispose of in accordance with local, state or federal laws.FCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Packaging (in.)	26.54 x 18.98 x 18.66
Physical (mm)600 x 135 x 115Net (lbs)4.86Gross (lbs)28.66Gross (kg)4.86One-year limited warranty on parts and laborNet (lbs)Please dispose of in accordance with local, state or federal laws.FCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Physical (in.)	23.62 x 5.31 x 4.53
Net (lbs)4.86Gross (lbs)28.66Gross (kg)4.86WarrantyOne-year limited warranty on parts and laborNet (lbs)Please dispose of in accordance with local, state or federal laws.RegulationsFCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Packaging (mm)	674 x 482 x 474
Gross (lbs)28.66Gross (kg)4.86WarrantyOne-year limited warranty on parts and laborRecycle/DisposalPlease dispose of in accordance with local, state or federal laws.FCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Physical (mm)	600 x 135 x 115
Gross (kg)4.86WarrantyOne-year limited warranty on parts and laborRecycle/DisposalPlease dispose of in accordance with local, state or federal laws.RegulationsFCC, FCC ID, CE, IC ID, LVDPACKAGE CONTENTSVB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Net (lbs)	4.86
Warranty One-year limited warranty on parts and labor Recycle/Disposal Please dispose of in accordance with local, state or federal laws. Regulations FCC, FCC ID, CE, IC ID, LVD PACKAGE CONTENTS VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Gross (lbs)	28.66
Recycle/Disposal Please dispose of in accordance with local, state or federal laws. Regulations FCC, FCC ID, CE, IC ID, LVD VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Gross (kg)	4.86
Regulations FCC, FCC ID, CE, IC ID, LVD PACKAGE CONTENTS VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Warranty	One-year limited warranty on parts and labor
PACKAGE CONTENTS VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6	Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Wall Anchor x 6	Regulations	FCC, FCC ID, CE, IC ID, LVD
UPC: 766907010909	PACKAGE CONTENTS	
	UPC: 766907010909	







Contact Sales ViewSonic.com

888.881.8781 email: salesinfo@viewsonic.com