


CDP4235


## Key Features

---


- 42" full HD 1920x1080p resolution
- Thin 19.5mm bezel width
- Designed for 24/7 applications



42  
DISPLAY



PANEL



RESOLUTION

## Product Description

---

***\*This product has been replaced by [CDE4200-L](#).***

ViewSonic's new CDP4235 Full HD Commercial display features a FHD 1920x1080 panel with 4000:1 contrast and Intel's Open Pluggable Specification (OPS) for applications requiring an integrated media player. Additional features include versatile inputs - HDMI, DVI, VGA, S video and composite, YPbPr and built in 10W x 2 speakers. The CDP4235 will support up to a 5x5 display video wall with internal clock and scheduler. RS232 daisy chain and RJ45 are provided for remote control.

## Specifications

---

### More Information

UPC	766907631111
Internal Speakers	10W (x2)
HDMI In	1
VGA	1

<b>Intel® OPS Slot In (80-pin)</b>	1
<b>Consumption (typical)</b>	210W
<b>Humidity (non-condensing)</b>	10-80%
<b>Physical (in.)</b>	39.04" x 24.4" x 12.98"
<b>Physical Without Stand (in.)</b>	39.04" x 22.9" x 4.52"
<b>Physical (mm)</b>	991.6mm x 621mm x 329.8mm
<b>Physical Without Stand (mm)</b>	991.6mm x 584mm x 115.5mm
<b>VESA Compatible</b>	400 x 400 mm
<b>Package Contents</b>	LCD display, power cable, remote control with batteries, User Guide CD
<b>Regulations</b>	FCC, ICES003, UL, cUL, CE, CB, C-Tick, BSM
<b>Classification</b>	Discontinued
<b>Screen Size</b>	42
<b>Light Source</b>	LCD
<b>Display Resolution</b>	1920 x 1080
<b>Aspect Ratio</b>	16:9
<b>Static Contrast Ratio</b>	4,000:1
<b>Backlight Life (Hours)</b>	50,000
<b>Brightness</b>	450 cd/m2
<b>Response Time (Typical GTG)</b>	11ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Panel Surface</b>	Anti-glare, Hard coating 3H

UPC: 766907631111



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)

888.881.8781  
 email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)