


TD2430-S


Key Features

REFURBISHED


- 10-point Projected Capacitive Touch
- SuperClear® MVA-type panel technology
- Frameless Design
- Versatile Connectivity
- Durable, Scratch-resistant Screen



24
DISPLAY



MVA
PANEL



1920 x 1080
RESOLUTION



Product Description

Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic® TD2430 is a 24" (23.6" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2430 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows 10, and certain Android and Linux versions.* With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more. *Supports Windows 7/8/10, Linux 2.6.38 or later, and Android 4.0 or later.

Specifications

	More Information
UPC	766907904512
Screen Size	24
Viewable Area (in.)	23.6
Display Resolution	1920 x 1080
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	50,000,000:1
Brightness	250 cd/m2
Backlight Life (Hours)	40,000

Response Time (Typical GTG)	25ms
Panel Type	MVA
Colors	16.7M
Viewing Angles	178° horizontal, 178° vertical
Light Source	WLED
Panel Surface	7H Scratch Resistant Surface Hardness
Aspect Ratio	16:9
PC Resolution (max)	1920 x 1080
Touch Technology	Projective Capacitive
Touch Points	10-Point Touch
USB 3.0 Type A	2
USB 3.0 Type B	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2.5W (x2)
Frequency Horizontal	Analog: 24 ~ 82KHz, Digital: 50 ~ 76Hz
Frequency Vertical	Analog: 15 ~ 82KHz, Digital: 50 ~ 76Hz
Analog Sync	Separate Sync / Composite Sync / Sync on Green, TMDS, PCI-E
Eco Mode (Conserve)	19W
Eco Mode (optimized)	22W
Consumption (typical)	25W
Consumption (max)	28W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Physical Controls	1, 2, Up, Down, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
Tilt (Forward/Back)	20° - 53°, 90° (Flat)
Kensington Lock Slot	1
VESA Compatible	100 x 100 mm
Gross (kg)	5.4
Net Without Stand (kg)	7.1
Net (lbs)	11.6

Gross (lbs)	15.6
Packaging (mm)	643 x 435 x 140
Physical (mm)	573 x 353 x 47
Packaging (in.)	25.3 x 17.1 x 5.5
Physical (in.)	22.6 x 13.9 x 1.9
Regulations	cTUVus, FCC-B w/ ICES003, DOE Energy Star 7.0, DOE EPEAT, TUV-MX-CoC, Mexico Energy
Package Contents	LCD Display, AC/DC Adapter, Power Cable (1.5m), HDMI Cable (1.5m), USB3.0 Upstream Cable (1.5m), Audio Cable (1.5m), Quick Start Guide, ViewSonic Wizard CD-ROM
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued, Refurbished

UPC: 766907904512



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com