


VG2453-S


Key Features

REFURBISHED


- SuperClear IPS Panel Technology
- Seamless Viewing Experience
- Versatile Connectivity
- Ergonomic Design
- Full HD 1080p Resolution



24
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION



Product Description

With future-proof connectivity and advanced ergonomics, the ViewSonic® VG2453 is a productivity-boosting monitor perfect for corporate, government, and education environments. Designed with SuperClear® IPS panel technology for wide-angle viewing and incredibly vivid colors, this monitor also features a 3-sided frameless design for a seamless viewing experience in multi-monitor setups. For maximum comfort and a customized fit, a robust fully ergonomic stand gives you tilt, pivot, swivel, and height-adjustable options. In addition, VDI client endpoints can be easily attached to the stand's integrated client mount, saving desktop space and minimizing cable clutter without interfering with ergonomic functionality. Extensive connectivity options include VGA, HDMI, DisplayPort, and Mini DisplayPort so that you can connect to a variety of HD and analog devices - today and tomorrow.

Specifications

More Information

UPC	766907903416
Screen Size	24
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	WLED

Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6-bit+A-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920 x 1080
USB 3.0 Type A	2
USB 3.0 Type B	1
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Mini DisplayPort	1
Internal Speakers	2-watt (x2)
Eco Mode (Conserve)	15W
Eco Mode (optimized)	19W
Consumption (typical)	21W
Consumption (max)	45W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2, Up, Down, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Analog Sync	Separate Sync / Composite Sync / Sync on Green
Digital Sync	TMDS, PCI-E
Height Adjust	135 mm / 5.3 in

Swivel	360°
Pivot (Right/Left)	90° / 0°
Tilt (Forward/Back)	5° / 20°
Net (lbs)	11.4
Net Without Stand (lbs)	6.9
Gross (lbs)	14.9
Net (kg)	5.2
Net Without Stand (kg)	3.1
Gross (kg)	6.8
Packaging (in.)	27.1 x 16.3 x 7.6
Physical (in.)	21.3 x 20.4 x 9.2
Physical Without Stand (in.)	21.3 x 16.3 x 1.8
Packaging (mm)	688 x 415 x 193
Physical (mm)	540 x 518 x 233
Physical Without Stand (mm)	540 x 324 x 46
Regulations	cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT, MX-CoC, Mexico Energy
Package Contents	LCD Display, Power Cable (1.5m), Mini DP to DP Cable (1.5m), USB3.0 Upstream Cable (1.5m), Quick Start Guide, ViewSonic Wizard CD-ROM
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907903416



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com