


VA2746MH-LED-S


Key Features

REFURBISHED


- Full HD 1080p Resolution
- Enhanced Viewing Comfort
- The Power of HDMI
- Dual Integrated Speakers



27
DISPLAY



TN
PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® VA2746mh-LED is a 27" widescreen monitor with an LED backlight and glossy, thin-bezel design ideal for use in the home or at the office. With Full HD 1920x1080 resolution and a 50M:1 MEGA Dynamic Contrast Ratio, the VA2746mh-LED delivers stunning brightness and contrast, while a quick 5ms response time ensures crisp pictures and smooth playback. As a complete multimedia package, the display also includes a pair of integrated speakers. VGA and HDMI inputs provide flexible and convenient connectivity, while a VESA-mountable design offers additional mount flexibility. With an environmental friendly LED backlight and ViewSonic's proprietary Eco-mode, the VA2746mh-LED reduces users' total energy cost. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, make the VA2746mh-LED a great long-term investment.

Specifications

More Information

UPC	766907929010
Screen Size	27
Viewable Area (in.)	27
Panel Type	TN
Display Resolution	1920 x 1080
Static Contrast Ratio	1,200:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	WLED
Brightness	300 cd/m2

Colors	16.7M
Color Space Support	6-Bit+ HI-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	170° horizontal, 160° vertical
Backlight Life (Hours)	50,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	22W
Eco Mode (optimized)	28W
Consumption (typical)	30W
Consumption (max)	40W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 82KHz
Frequency Vertical	50 ~ 75Hz
Analog Sync	Separate Sync
Digital Sync	TMDS
Tilt (Forward/Back)	5° / 23°
Net (lbs)	11.6
Net Without Stand (lbs)	10.69
Gross (lbs)	14.99

Net (kg)	5.26
Net Without Stand (kg)	4.85
Gross (kg)	6.8
Packaging (in.)	28.11 x 20.67 x 5.55
Physical (in.)	25.4 x 17.4 x 9.75
Physical Without Stand (in.)	25.4 x 15.69 x 2.22
Packaging (mm)	714 x 525 x 141
Physical (mm)	645.26 x 442.08 x 247.59
Physical Without Stand (mm)	645.26 x 398.56 x 56.4
Regulations	cULus, FCC-B, ICES003, Energy Star 7.0, Mexico Energy, UL-MX-CoC, MEPS
Package Contents	VA2746mh-LED Display, Power Cable (1.5m), VGA Cable (1.5m), Audio Cable (1.5m), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907929010



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com