


LD135-151 - 135" DISPLAY, 1920 X 1080 RESOLUTION, 600-NIT BRIGHTNESS, 24/7

Key Features

- All-in-One Solution
- Powerful Embedded SoC Platform
- Multi-Panel Modular Design for Easy Installation
- Vivid Colors and Stunning Images
- AV Control System Compatible











Product **Description**

The ViewSonic® LD135-151 is a premium all-in-one direct view LED commercial display. With a huge 135" screen size, the LD135-151 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 1.5mm fine pixel pitch, 600-nit high brightness, 4,440Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut.

Integrated ViewBoard® Cast screen sharing software* (along with optional ViewSonic vCastSender app), enables both on-site and online attendees to participate in video conferences and simultaneously share content. Equipped with twin dual-core processors, 4GB RAM, and 32GB of internal memory, the LD135-151 can play multimedia from internal storage or a USB flash drive 24 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic LD135-151 is also suitable for a wide array of diverse signage applications.

*Chrome, Android, Windows, Mac OS, and iOS compliant

Specifications

UPC 766907008784 OS Android 8.0 Media Player Type Yes GPU Mult-core MailGS1 MPZ CPU M3751 W811 Memory 4GB D0R4 Storage 3268 (2668 available) Internal Speakers 5W (v.2) HDMI In 2 HDMI 1.4 Out (with HDCP 1.4) 1 HDMI 1.4 Out (with HDCP 1.4) 1 USB 3.0 1 USB 2.0 2 USB 2.0 1 2 RES222 1 Ethernet LAN (RJ4S) 1 It In 1 Intel® OPS Siot in (80-pin) 1 Voltage 100-240V+/-10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,900W Remote Control Yes Remote Control Yes Remote Control Yes Temperature 29.104*F(0-40*C) Humidity (non-condensing) 29.08% Met (lba) 29.1 O	More Information	
Media Player Type Yes GPU Mult-core MaliGS1 MP2 CPU Hi3751 V811 Memory 4 GB DDR4 Storage 32EB (26GB available) Internal Speakers SW (x2) HDMI In 2 HDMI 1.4 Out (with HDCP 1.4) 1 4 HDMI 1.4 Out 1 USB 3.0 1 USB 2.0 2 USB 2.0 Type B 1 R S232 1 Ethernet LAN (RJ45) 1 I IR in 1 Intel® OPS Siot in (80-pin) 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (typical) 2,900W Consumption (typical) 2,030W Stand-by <0.5W	UPC	766907008784
GPU Mult-core MailGS1 MP2 CPU Hi3751 V811 Memory 4GB DDR4 Storage 32GB (26GB available) Internal Speakers 5W (x2) HDMI In 2 HDMI 1.4 Out (with HDCP 1.4) 1 HDMI 1.4 Out (with HDCP 1.4) 1 USB 3.0 1 USB 2.0 2 USB 2.0 2 USB 2.0 Type B 1 R 5232 1 Ethernet LAN (RI45) 1 I Intel® OPS Slot in (80-pin) 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W	os	Android 8.0
CPU H3751 V811 Memory 4GB DDR4 Storage 32GB (26GB available) Internal Speakers 5W (x2) HDMI In 2 HDMI 1.4 Out (with HDCP 1.4) 1 4 HDMI 1.4 Out 1 3.5mm Audio Out 1 USB 2.0 2 USB 2.0 Type B 1 RS232 1 Ethernet LAN (RJ45) 1 IR in 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by 0.5W On Screen Display Yes Remote Control Yes Remote Control 20.80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Media Player Type	Yes
Memory 4GB DDR4 Storage 32GB (2GGB available) Internal Speakers 5W (x2) HDMI In 2 HDMI 1.4 Out (with HDCP 1.4) 1 4 HDMI 1.4 Out 1 USB 3.0 1 USB 2.0 2 USB 2.0 Type B 1 RS232 1 Ethernet LAN (RJ45) 1 IR in 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Remote Control Yes Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	GPU	Mult-core MaliG51 MP2
Storage 32GB (26GB available)	СРИ	Hi3751 V811
Internal Speakers 5W (x2) HDMI 1.4 Out (with HDCP 1.4) 1 HDMI 1.4 Out (with HDCP 1.4) 1 JSB 3.0	Memory	4GB DDR4
HDMI In 2 HDMI 1.4 Out (with HDCP 1.4) 1 HDMI 1.4 Out 1 3.5mm Audio Out 1 USB 3.0 1 USB 2.0 Type B 1 RS232 1 Ethernet LAN (RJ45) 1 IR in 1 Intel® OPS Slot In (80-pin) 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Remote Control Yes Humildity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 7.09 × 29.3 × 33.5	Storage	32GB (26GB available)
HDMI 1.4 Out (with HDCP 1.4) 1 HDMI 1.4 Out 1 3.5mm Audio Out 1 USB 3.0 1 USB 2.0 2 USB 2.0 Type B 1 RS232 1 Ethernet LAN (RJ45) 1 IR in 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,900W On Screen Display Yes Remote Control Yes Remote Control Yes Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 7.09 x 29.3 x 33.5	Internal Speakers	5W (x2)
HDMI 1.4 Out 1	HDMI In	2
3.5mm Audio Out 1	HDMI 1.4 Out (with HDCP 1.4)	1
USB 3.0 2 USB 2.0 Type B 1 RS232 1 Ethernet LAN (R/45) 1 IR in 1 Intel® OPS Slot In (80-pin) 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 29-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	HDMI 1.4 Out	1
USB 2.0 Type B 1 RS232 1 Ethernet LAN (RJ45) 1 IR in 1 Intel® OPS Slot In (80-pin) 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,990W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 1 Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	3.5mm Audio Out	1
NSB 2.0 Type B 1	USB 3.0	1
RS232 1 Ethernet LAN (RJ45) 1 IR in 1 Intel® OPS Slot in (80-pin) 1 Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	USB 2.0	2
Ethernet LAN (R)45) 1 1 1 1	USB 2.0 Type B	1
IR in 1	RS232	1
Intel® OPS Slot In (80-pin) 1 1 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) 2,900W 2,900W 2,030W 3,000 2,030W 3,000 3	Ethernet LAN (RJ45)	1
Voltage 100-240V+/- 10%, (100-120V/30A, 50/60Hz; 220-240V/15A) Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	IR in	1
Consumption (max) 2,900W Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Intel® OPS Slot In (80-pin)	1
Consumption (typical) 2,030W Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Voltage	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A)
Stand-by <0.5W On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Consumption (max)	2,900W
On Screen Display Yes Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Consumption (typical)	2,030W
Remote Control Yes Temperature 32-104° F (0 - 40° C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Stand-by	<0.5W
Temperature 32-104º F (0 - 40º C) Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	On Screen Display	Yes
Humidity (non-condensing) 20-80% Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Remote Control	Yes
Net (lbs) 297.6 Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Temperature	32-104º F (0 - 40º C)
Gross (lbs) 529.1 Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Humidity (non-condensing)	20-80%
Net (kg) 135.0 Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Net (lbs)	297.6
Gross (kg) 240.0 Packaging (in.) 70.9 x 29.3 x 33.5	Gross (lbs)	529.1
Packaging (in.) 70.9 x 29.3 x 33.5	Net (kg)	135.0
	Gross (kg)	240.0
Physical (in.) 118.9 x 71.1 x 1.4	Packaging (in.)	70.9 x 29.3 x 33.5
	Physical (in.)	118.9 x 71.1 x 1.4

1800 x 745.0 x 850.0 Packaging (mm) Physical (mm) 3020.9 x 1805.9 x 35.0 **AV Control** AMX Certified, Crestron Certified, Extron Certified 5-year limited warranty on parts and labor, on-site service Warranty Recycle/Disposal Please dispose of in accordance with local, state or federal laws. Power Cord, Remote Control, QSG, Wall-mount x 1, Maintenance Tool (LD-MK-001) x 1, Spare Modules (LED **Package Contents** PCB x 2) Regulations cTUVus, FCC, RoHS, Mexico CoC, Mexico Energy Wifi 802.11ac (2.4GHz/5GHz) **Display Type** Direct View LED 135 **Screen Size** Viewable Area (in.) 135 Fine Pixel Pitch LED **Light Source** LED Pitch Size (mm) 1.56 14 bits **LED Grayscale** 1920 x 1080 **Display Resolution** 4,440Hz **Refresh Rate Aspect Ratio** 16:9 **Static Contrast Ratio** 6,000:1 **Backlight Life (Hours)** 100,000 600-nit **Brightness Viewing Angles** 160º horizontal, 160º vertical 24/7 **Operation Rating**

UPC: 766907008784







Contact Sales ViewSonic.com

888.881.8781 Semail: salesinfo@viewsonic.com