

VP3256-4K - 32" COLORPRO™ 4K UHD IPS MONITOR WITH 65W USB C, SRGB, HDR10 AND PANTONE VALIDATED


## **Key Features**

- 32 Inch 4K UHD (3840x2160p) IPS monitor with thin bezels, HDR10 and 60Hz refresh rate
- In addition to fast data, audio and video transfer, USB-C also provides quick 65W charging over a single cable
- Advanced ergonomics (tilt, swivel, pivot and height) for all-day comfort
- · Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- 100% sRGB, EBU, SMPTE-C, and Rec. 709 color spaces and Delta E<2 accuracy
- This monitor has been certified as capable of reproducing Pantone Matching System colors
- Adaptive Sync technology enables smooth frame rates to aid you in battle
- The VP3256-4K supports laptops, PCs, Macs and more with USB-C, HDMI, USB and DisplayPort inputs










IPS PANEL



3840 x 2160 **RESOLUTION** 



## Product **Description**

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP3256-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel for 100% sRGB and a sleek 3-sided frameless design, the VP3256-4K provides a near-seamless viewing experience. The VP3256-4K is equipped with USB-C for single cable connectivity to deliver video, audio, and 65W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your customers will see, as well.

## **Specifications**

UPC	766907014532
Screen Size	32
Viewable Area (in.)	31.5
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	2
USB Type B	1
USB Type C	65W x 1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	32W
Eco Mode (optimized)	39W
Consumption (typical)	46W
Consumption (max)	125W
Voltage	100-240 VAC
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	TMDS, PCI-E, Micro-Packet: 15 ~ 136 KHz
Frequency Vertical	TMDS, PCI-E, Micro-Packet: 24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	1209
Pivot (Right/Left)	90º / 90º
Net (lbs)	24.0
Net Without Stand (lbs)	15.8
Gross (lbs)	33.7
Net (kg)	10.9
Net Without Stand (kg)	7.2
Gross (kg)	15.3
Packaging (in.)	33.1 x 20.5 x 12.8
Physical (in.)	28.2 x 20.2~25.4 x 10.4
Physical Without Stand (in.)	28.2 x 16.7 x 2.6
Packaging (mm)	840.0 x 520.0 x 326.0
Physical (mm)	715.0 x 514.0~644.0 x 265.0
Physical Without Stand (mm)	715.0 x 423.0 x 66.0
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Package Contents	VP3256-4K, Power Cable, USB-C Cable, HDMI cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907014532







Contact Sales
ViewSonic.com
888.881.8781 email:
salesinfo@viewsonic.com