

VP2756-4K-S


Key Features

REFURBISHED


- Pantone Validated Display
- Designer Mode
- Hardware calibration ready
- vDisplayManager
- Reduce Clutter With Single-Cable Solution



27
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2756-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek 3-sided frameless design, the VP2756-4K provides a near-seamless viewing experience ideal for multi-monitor setups. The VP2756-4K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your clients and customers will see as well.

Specifications

[More Information](#)

UPC

766907017762

Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	2
USB Type B	1
USB Type C	1
HDMI 2.0 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	37.5W
Eco Mode (optimized)	39.5W
Consumption (typical)	42W
Consumption (max)	122W
Voltage	100-240 VAC
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%

VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 136 KHz
Frequency Vertical	24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	60°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 21°
Net (lbs)	15.1
Net Without Stand (lbs)	9.8
Gross (lbs)	21.0
Net (kg)	6.9
Net Without Stand (kg)	4.4
Gross (kg)	9.5
Packaging (in.)	21.9 x 18.3 x 8.9
Physical (in.)	24.1 x 16.15~21.27 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.1
Packaging (mm)	740.0 x 465.0 x 225.0
Physical (mm)	613.0 x 410.0~540.0 x 215.0
Physical Without Stand (mm)	613.0 x 363.0 x 53.0
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Package Contents	VP2756-4K, Power Cable, USB-C Cable, HDMI cable, UAB-A/B Cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Classification	Refurbished

UPC: 766907017762



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com