

LDM216-251 - 216" ALL-IN-ONE MAINSTREAM FULL HD DIRECT VIEW LED DISPLAY

Key Features

- High-Impact Messaging
- Simple and Easy Setup
- Amazing Audio-Visual Experience
- Device Management Made Easy
- Easy Maintenance










PANEL



1920x1080 RESOLUTION



Product **Description**

The ViewSonic® LDM216-251 is an innovative All-in-One Direct View LED display. With a huge 216" screen size, the LDM216-251 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 2.5mm fine pixel pitch, 600-nit high brightness, 3,840Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut. What's more, its ultra-slim 35mm thickness and bezel-free design delivers sleek looks whether its hanging on a wall or mounted on an optional aluminum floor stand. Despite its huge screen size, a front-assembly modular design enables easy delivery, installation, and maintenance. And with remote configuration and content management system support, the ViewSonic LDM1216-2511 is also suitable for a wide array of diverse signage applications.

Specifications

| UPC | 766907014488 |
|--------------------------------|---|
| os | Android 8.0 |
| СРИ | Hi3751 V811 |
| Memory | 4GB DDR4 |
| Storage | 32GB (26GB available) |
| Internal Speakers | 5W (x2) |
| PC Resolution (max) | 1920x1080 |
| Mac® Resolution (max) | 1920x1080 |
| HDMI 1.4 (with HDCP 1.4) | 2 |
| HDMI 1.4 Out (with HDCP 1.4) | 1 |
| 3.5mm Audio Out | 1 |
| USB 3.0 | 1 |
| USB 2.0 | 2 |
| USB 2.0 Type B | 1 |
| RS232 | 1 |
| Ethernet LAN (RJ45) | 1 |
| IR in | 1 |
| Intel® OPS Slot In (80-pin) | 1 |
| Voltage | 100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A) |
| Consumption (max) | 4900W |
| Consumption (typical) | 3430W |
| Stand-by | <0.5W |
| Temperature | 32-104º F (0 - 40º C) |
| Humidity (non-condensing) | 20-80% |
| Net (lbs) | 750 |
| Gross (lbs) | 992 |
| Net (kg) | 340 |
| Gross (kg) | 450 |
| Packaging (in.) | 109.4 x 33.5 x 40.2 |
| Physical (in.) | 189.8 x 110.9 x 1.4 |
| Physical with Wall Mount (in.) | 189.8 x 110.9 x 2.2 |
| Packaging (mm) | 2780.0 x 850.0 x 1020.0 |
| Physical (mm) | 4820.95 x 2818.45 x 35.0 |
| Physical with Wall Mount (mm) | 4820.95 x 2818.45 x 56.0 |
| Warranty | Three (3) years from the date of first consumer purchase for parts and labor. |
| Display Type | Direct View LED |

| Screen Size | 216 |
|------------------------|--------------------------------|
| Viewable Area (in.) | 216 |
| Orientation | Landscape |
| Light Source | Fine Pixel Pitch LED |
| LED Pitch Size (mm) | 2.5 |
| LED Grayscale | 14 bits |
| Display Resolution | 1920 x 1080 |
| Refresh Rate | 3,840Hz |
| Aspect Ratio | 16:9 |
| Static Contrast Ratio | 6,000:1 |
| Backlight Life (Hours) | 100,000 |
| Brightness | 600-nit |
| Viewing Angles | 160º horizontal, 160º vertical |
| | |

UPC: 766907014488





Contact Sales ViewSonic.com 888.881.8781 email: salesinfo@viewsonic.com