

TD2211 - 22" 1080P SINGLE POINT RESISTIVE TOUCH MONITOR WITH USB, HDMI, DVI AND VGA

Key Features

- Industrial-grade touch display ideal for commercial use
- Greater clarity with SuperClear® MVA panel technology
- Flexible connectivity with HDMI, DVI and VGA ports
- Supports laptops, PCs, Macs and POS Systems



22
DISPLAY



MVA
PANEL



1920 x 1080
RESOLUTION



Product Description

Featuring a robust 22" touchscreen, the ViewSonic® TD2211 touch display is ideal for use in retail, POS and commercial environments.

Each display comes equipped with resistive touch technology, making it responsive to hands, gloves and styluses alike.

The TD2211 combines Full HD resolution with a 20M:1 dynamic contrast ratio to deliver crystal clear images.

Enjoy flexible connectivity options including HDMI, VGA, DVI and USB ports as well as a VESA-compatible mount design that makes it easy to transform your device into a wall mounted display.

Specifications

	More Information
UPC	766907022988
Screen Size	22
Viewable Area (in.)	21.5
Display Resolution	1920 x 1080
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	20,000,000:1
Brightness	250 cd/m2
Backlight Life (Hours)	30,000
Response Time (Typical GTG)	6.8ms
Panel Type	MVA
Colors	16.7M
Color Space Support	8 bits
Viewing Angles	178° horizontal, 178° vertical
Light Source	LED
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Aspect Ratio	16:9
Refresh Rate	75Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
Touch Technology	Resistive
Touch Points	1-Point Touch
USB Type A	2
USB Type B	1
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
DVI-D	1
HDMI 1.4 In	1
Internal Speakers	2W (x2)
Frequency Horizontal	HDMI 1.4 = 24 ~ 84 KHz / RGB Analog / DVI-D = 24 ~ 82 KHz
Frequency Vertical	HDMI 1.4 / RGB Analog / DVI-D = 50 ~ 75 Hz
Eco Mode (Conserve)	18w
Eco Mode (optimized)	21w

Consumption (typical)	23.5w
Consumption (max)	26.8w
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5w
Physical Controls	1, 2, Up, Down, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
Tilt (Forward/Back)	5° / 20°
Kensington Lock Slot	1
VESA Compatible	100 x 100 mm
Gross (kg)	6.1
Net (kg)	4.4
Net Without Stand (kg)	3.5
Net (lbs)	9.6
Net Without Stand (lbs)	7.7
Gross (lbs)	13.4
Packaging (mm)	580 mm (W) x 445 mm (H) x 200 mm (D)
Physical (mm)	519 mm (W) x 377 mm (H) x 240 mm (D)
Physical Without Stand (mm)	519 mm (W) x 308 mm (H) x 55 mm (D)
Packaging (in.)	22.8 " (W) x 17.5 " (H) x 7.9 " (D)
Physical (in.)	20.4 " (W) x 14.8 " (H) x 9.4 " (D)
Physical Without Stand (in.)	20.4 " (W) x 12.1 " (H) x 2.2 " (D)
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT Silver, CEC, NOM, Mexico Energy
Package Contents	LCD Display, Power Cable, HDMI Cable, USB Type A/B cable, Audio Cable, Quick Start Guide
Warranty	Three-year limited warranty on parts, labor and backlight
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907022988



Contact Sales
ViewSonic.com

888.881.8781
 email:
salesinfo@viewsonic.com