

LD216-251 - 216" DISPLAY, 1920 X 1080 RESOLUTION, 600-NIT BRIGHTNESS, 24/7

Key Features

- All-in-One Solution
- Powerful Embedded SoC Platform
- Multi-Panel Modular Design for Easy Installation
- Vivid Colors and Stunning Images
- AV Control System Compatible
- Free Viewboard® Cast Content Sharing Software




216
DISPLAY



PANEL



1920x1080
RESOLUTION



Product Description

The ViewSonic® LD216-251 is a premium all-in-one direct view LED commercial display. With a huge 216" screen size, the LD216-251 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 2.5mm fine pixel pitch, 600-nit high brightness, 4,440Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut.

Integrated ViewBoard® Cast screen sharing software* (along with optional ViewSonic vCastSender app), enables both on-site and online attendees to participate in video conferences and simultaneously share content. Equipped with twin dual-core processors, 4GB RAM, and 32GB of internal memory, the LD216-251 can play multimedia from internal storage or a USB flash drive 24 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic LD216-251 is also suitable for a wide array of diverse signage applications.



*Chrome, Android, Windows, Mac OS, and iOS compliant

Specifications

More Information	
UPC	766907010442
Display Type	Direct View LED
Screen Size	216
Viewable Area (in.)	216
Light Source	Fine Pixel Pitch LED
LED Pitch Size (mm)	2.5
LED Grayscale	14 bits
Display Resolution	1920 x 1080
Refresh Rate	4,440Hz
Aspect Ratio	16:9
Static Contrast Ratio	6,000:1
Backlight Life (Hours)	100,000
Brightness	600-nit
Viewing Angles	160° horizontal, 160° vertical
Operation Rating	24/7
Wifi	802.11ac (2.4GHz/5GHz)
OS	Android 8.0
Media Player Type	Yes
GPU	Multi-core MaliG51 MP2
CPU	Hi3751 V811
Memory	4GB DDR4
Storage	32GB (26GB available)
Internal Speakers	5W (x2)
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
HDMI 1.4 In	1
HDMI 1.4 (with HDCP 1.4)	1
HDMI 1.4 Out (with HDCP 1.4)	1
HDMI 1.4 Out	1
3.5mm Audio Out	1
USB 3.0	1
USB 2.0	2
USB 2.0 Type B	1

RS232	1
Ethernet LAN (RJ45)	1
IR in	1
Intel® OPS Slot In (80-pin)	1
Voltage	100-240V+/- 10%, (100-120V/30A, 50/60Hz ; 220-240V/15A)
Consumption (max)	4,900W
Consumption (typical)	3,430W
Stand-by	<0.5W
Temperature	41-104° F (5 - 40° C)
Humidity (non-condensing)	20-80%
Net (lbs)	750.0
Gross (lbs)	992.0
Net (kg)	340.0
Gross (kg)	450.0
Packaging (in.)	109.4 x 40.2 x 33.5
Physical (in.)	189.8 x110.9 x 1.38
Physical with Wall Mount (in.)	189.8 x 110.9 x 2.2
Packaging (mm)	2780.0 x 1020.0 x 850.0
Physical (mm)	4820.0 x 2818.0 x 35.0
Physical with Wall Mount (mm)	4820.0 x 2818.0 x 56.0
Warranty	3-year limited warranty on parts and labor, on-site service
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Package Contents	Power Cord, Remote Control, QSG, Wall-mount, Maintenance Tool (LD-MK-001), USB Cable (A-to-B), Spart Modules (LED PCB x 2)
Regulations	cTUVus, FCC, RoHS, Mexico CoC, Mexico Energy

UPC: 766907010442



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com