

# V3D241wm-LED

WW First 3D-LED DISPLAY

## Get Ready to be Amazed



- > **3D gaming with ViewSonic**  
This ViewSonic 3D Monitors offers a pure, revolutionary 120Hz frame rate combined with ultra-fast 2ms video response; a technology partnership dedicated to delivering a truly immersive, ultimate gaming experience just for you.
- > **Full HD 1080p performance for unsurpassed HD viewing**
- > **Impressive 20,000,000:1 dynamic contrast ratio provides greater detail and definition**  
Provides darker black levels and better overall front-of-screen performance.
- > **High brightness to reflect the true colour**  
300 nits high brightness delivers precise accurate colour to realistically display a full array of brilliant shades and hues.
- > **Eco-mode automatically reduces power consumption and can extend backlight life and reduce operating power consumption by up to 40%**
- > **SRS Premium Sounds**  
The two watt built-in audio speakers provide superior audio quality for all multimedia applications while reducing desktop space required by separate speakers.
- > **Windows® 7 certified**

Model Name	V3D241wm-LED	
LCD	Size Optimum Resolution Brightness (cd/m <sup>2</sup> ) Contrast Ratio (typical) Dynamic Contrast Ratio Viewing Angle (CR $\geq$ 10) Response Time (ms) Pixel Pitch (H $\times$ V) Panel Surface Colour Support	60CM/23.6"wide Colour Active Matrix TFT LCD with 16:9 aspect ratio 1920 $\times$ 1080 300 (typical) 1000:1 20,000,000:1 170° (H), 160° (V) 5 (typical) / 2ms (G to G) 0.2715 mm (H) x 0.2715mm (V) Anti-Glare, Hard coating (3H) 16.7 Millions
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync / Composite Sync / SOG 24-83kHz / 50-76Hz
COMPATIBILITY	PC Mac	VGA up to 1920 $\times$ 1080 Non Interlaced 1920 $\times$ 1080 Non Interlaced
CONNECTOR	Analogue Digital Power Audio USB	1 $\times$ 15 pin mini D-sub DVI-D / HDMI Internal Power Adapter, 3-pin plug (CEE22) 1 $\times$ 3.5mm jack in/out USB type-B for 3Dglasses
SPEAKER POWER	Speaker Voltage Consumption (W) Save mode (W)	2w x 2 (SRS Premium Sounds) AC 100-240V (Universal); 50/60Hz(Switch) 35 W (typical) w/o Audio / 38 W (maximum) with Audio $\leq$ 1W
CONTROLS	Basic OnView / OSD	[1], [2], Power, Down[▼], Up[▲] Auto Image Adjust Contrast/Brightness, Input Select, D-SUB, DVI, HDMI PC, HDMI AV, Audio Adjust, Volume, mute, Audio input, Colour AdjustsRGB, 9300K, 7500K, 6500K, 5000K, User Colour [R, G,B], Information Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness,Dynamic Contrast, Response Time, Aspect Ratio, Display Mode, ECO Mode, Setup Menu, Language, Resolution Notice, OSD Position, OSDTimeout, OSD Background, Auto Power Off, Sleep, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 10 - 90 (%)
DIMENSIONS (W $\times$ H $\times$ D)	Physical (w/ stand)	563.6 mm (W) x417.7 mm (H)x260.8 mm (D)
WEIGHT	Net (w/ stand)	5.1 Kg
REGULATIONS		BSMI, CCC, PSB, C-Tick, CE, Ergo, Gost-R/Hygienic, Ukraine, FCC-B, ICES-B, WEEE, RoHS, Energy star 5.0, TCO 5.0
WALL MOUNT (mm)	VESA® Mount Compliant	100 $\times$ 100