

VA1931wa

47cm/ 18.5" Viewable Widescreen LCD

A Value Monitor Making Green Sense



- > **16:9 Aspect Ratio for distortion free HD experience**
- > **OSD/Power Lock Function**
When activated, the user-controlled OSD/, Power lock function prevents changes to monitor settings, maintaining an optimized image.
- > **Impressive 100,000:1 dynamic contrast ratio provides greater detail and definition**
Provides darker black levels and better overall front-of-screen performance.
- > **Aspect ratio adjustment ensures your images are never distorted regardless of signal source**
Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.
- > **Eco-mode automatically reduces power consumption and can extend backlight life.**
Reduce operating power consumption by up to 40%
- > **Stylish slim-bezel design with high-gloss, piano-black finish**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **Windows® 7 certified**



Model Name	VA1931 wa	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (typical) Dynamic Contrast Ratio Viewing Angle (CR≥10) Response Time (ms) Pixel Pitch (H×V) Panel Surface Light Source (Hours) Colour Support (Millions of colours)	47cm/ 19"(18.5") wide Colour TFT Active Matrix LCD 16:9 aspect ratio 1366×768 250 (typical) 1000:1 100,000:1 170° (H), 160° (V) 5ms (typical) 0.3 × 0.3 (mm) Anti-Glare, Hard coating (3H) 50,000 hrs (minimum) 16.7 M
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync 24-82kHz / 50-75Hz
COMPATIBILITY	PC Mac	VGA up to 1366×768 Non Interlaced 1366×768 Non Interlaced
CONNECTOR	Analogue	1×15 pin mini D-sub
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60Hz(Switch) 20 (typical) / 25(maximum) ≤0.5W
ERGONOMICS CONTROLS	Tilt Basic OnView / OSD	20~-5 degrees [1], [2], Power, Down[▼], Up[▲] Auto Image, AdjustContrast/Brightness Audio Adjust Volume, MuteColor Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Eco mode, Setup MenuLanguage Select, Resolution Notice, OSD Position, OSD Time out, OSD Background, Auto Power Off, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / - 4 - 140 (°F) 10 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	446.6 × 351.2 × 189.44 (mm), 17.6 × 13.8 × 7.5 (in)
WEIGHT	Net (w/ stand)	3.4kg / 7.5 lb
REGULATIONS		Global CB, WEEE, RoHS, REACH SVHC List, EuP, TCO5.0, Windows XP/ Vista Basic, CE, ERGO, GOST-R+Hygienic, UkrSEPRO, BSMI, PSB, C-TICK, KC, SASO, Energy Star 5.0 Windows® 7
WALL MOUNT (mm)	VESA® Mount Compliant	100mm × 100mm

ViewSonic® 

For more product information, visit us at www.viewsoniceurope.com

See the difference™