

VA916g

48cm/19" LCD DISPLAY



- > **100,000:1 Dynamic Contrast Ratio**
Provides for darker black levels and better overall front-of-screen performance.
- > **5ms video response delivers superior picture clarity**
- > **1280 x 1024 native resolution**
Incredible image detail for sharp text and graphics.
- > **Slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable-desktop real estate.
- > **OSD/power lock secures your settings**
Prevents changes to monitor settings and maintains an optimised image.
- > **OnView controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **TCO 5.0 and ENERGY STAR qualified**



Model Name	VA916g	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (Typical) Dynamic Contrast Ratio Viewing Angle (CR \geq 10 / CR \geq 5) Response Time (ms) Pixel Pitch (HxV) Panel Surface Light Source (Hours) Colour Support (Millions of colours)	48cm/19" TN colour TFT active matrix SXGA LCD 1280x1024 250 (Typical) 1000:1 100,000:1 170° horizontal, 160° vertical 5 (typical) 0.294 x 0.294 (mm) Anti-Glare 40,000 (Typ.) 16.7 Millions
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) H/V Sperate(TTL) 24-82kHz / 50-75Hz
COMPATIBILITY	PC Mac	VGA up to 1280x1024 Non Interlaced 1280x1024 Non Interlaced
CONNECTOR	Analogue Power	15-pin mini D-Sub 3-pin AC plug (CEE22)
POWER	Voltage Consumption (W) Start Mode(W)	AC 100-240V (Universal); 50/60Hz(auto switch), internal power supply 25 W (typical) <1W
CONTROLS	Basic OnView / OSD	Power, menu [1], up, down, select [2] Auto image adjust, contrast, brightness, ViewMatchcolour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), auto white balance, OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 20 - 90 (%)
DIMENSIONS (WxHxD mm)	Physical (w/ stand)	412(W) x 435(H) x 195(D)mm
WEIGHT	Net (w/ stand)	4.1 kg (9.02lbs)
REGULATIONS		TCO 5.0, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CE, CB, GOST-R, Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, KTL/MIC, BSMI, PSB, MPR II, TÜV-S, CCC, VCCI, WEEE, RoHS
WALL MOUNT (mm)	VESA® Mount Compliant	100 x 100