

# E96f+SB

## CRT MONITOR

19" (18" VIEWABLE) E<sup>2</sup> SERIES CRT

## Brilliant Performance

The ultra-stylish ViewSonic E96f+SB 19" CRT monitor offers AFFORDABLE QUALITY, PERFORMANCE AND RELIABILITY. Thanks to its PerfectFlat<sup>®</sup> screen you'll view edge-to-edge, distortion-free images with minimised reflection and glare. With an easy touch of the UltraBrite button, choose between HIGH-BRIGHTNESS TO ENHANCE GAMING, DVD, TV AND GRAPHICS or normal brightness for word processing, spreadsheets and text. The ultra-fine 0.20mm horizontal dot pitch delivers precise picture definition when viewing everyday applications. Adjust your screen with the OnView<sup>®</sup> controls and secure them with the OSD lock function to ensure OPTIMUM SCREEN PERFORMANCE. Perfect for demanding business, SOHO and education applications.



### RELIABLE, LARGE SCREEN PERFORMANCE.

> **PerfectFlat<sup>®</sup> technology for distortion-free images**

ViewSonic's PerfectFlat screen technology ensures realistically proportioned, precise images that are crisp all the way to the edge. It also reduces ambient light reflections, image distortion and eye fatigue to provide added viewing comfort and a higher quality picture.

> **UltraBrite<sup>™</sup> technology for brilliant graphics**

Games, TV, DVD and 3D video come alive with UltraBrite 5X technology. With up to 5 times the brightness of typical CRTs, you'll get saturated, photo-realistic images.

> **0.20mm horizontal dot pitch, 0.25mm ultra-fine diagonal dot pitch**

Ultra-fine dot pitch delivers clear, crisp images with precise picture definition, even at the highest resolution.

> **See it all with 1792 x 1344 maximum resolution**

Displays a maximum resolution of 1792 x 1344; 1280 x 1024 @ 80Hz flicker-free refresh rate for easy-on-the-eyes viewing.

|        |      |         |
|--------|------|---------|
| 1280 x | 1024 | @ 80Hz  |
| 1152 x | 864  | @ 95Hz  |
| 1024 x | 768  | @ 105Hz |
| 800 x  | 600  | @ 132Hz |
| 640 x  | 480  | @ 163Hz |

> **OnView<sup>®</sup> controls including ViewMatch<sup>®</sup> technology**

Screen adjustments are made via an on-screen menu using simple controls.

> **OSD lock secures your settings**

When activated, the user-controlled OSD lock function prevents changes to monitor settings, maintaining an optimised image.

> **PC and Mac<sup>®</sup> compatible**

# E96f+SB

## 19" (18" VIEWABLE) PERFECTFLAT CRT COLOUR MONITOR



|                             |                   |   |
|-----------------------------|-------------------|---|
| <b>CRT</b>                  | Type              | 19" (18" viewable) CRT, 90° deflection, PerfectFlat   |
|                             | Dot Pitch         | 0.20mm horizontal x 0.14mm vertical, 0.25mm diagonal  |
|                             | Phosphor          | RGB P22 (Cd free)   |
|                             | Glass Surface     | Tint: (TM ~ 53.6%), anti-reflection, anti-static  |
| <b>INPUT SIGNAL</b>         | Video             | RGB analogue (0.7 Vp-p, 75 ohms)  |
|                             | Frequency         | Fh: 30 - 86kHz, Fv: 50 - 160Hz  |
|                             | Sync              | H/V separated (TTL)   |
| <b>COMPATIBILITY</b>        | PC                | PC and compatible (from VGA up to 1792 x 1344)  |
|                             | Mac <sup>®1</sup> | Power Mac™ G3/G4 (from 640 x 480 up to 1152 x 864)  |
| <b>CONNECTORS</b>           | Signal            | 15-pin mini D-sub   |
|                             | Power             | 3-pin plug (IEC320)   |
| <b>POWER</b>                | Voltage           | AC 100 - 240V, 50/60Hz (+/-3Hz) (auto-switch)   |
|                             | Consumption       | 55 watts (typ.)   |
| <b>USER CONTROLS</b>        | Physical          | Power on/off, menu, up, down, select, UltraBrite  |
|                             | OSD               | Contrast, brightness, zoom, H/V size, H/V position, pincushion, pin balance, trapezoid, parallelogram, tilt, moiré reduction, degauss, ViewMatch® colour (9300k, 6500k, 5000k user), ViewMeter, OSD position, language, OSD lock, Memory recall |
| <b>VIDEO INPUT</b>          | Bandwidth         | 210MHz (typ.)   |
| <b>MISCONVERGENCE</b>       |                   | 0.25mm (max.) at centre<br>0.35mm (max.) at corner  |
| <b>PROGRAMMABLE</b>         | Factory           | 10  |
| <b>MODES</b>                | User              | 12  |
| <b>DISPLAY AREA</b>         | Factory Setting   | 352mm (H) x 264mm (V) (typ.)  |
|                             | Maximum Scan      | 360mm (H) x 270mm (V) (depending on signal timing used)   |
| <b>OPERATING CONDITIONS</b> | Temperature       | 0°C to 40°C   |
|                             | Humidity          | 5% to 95% (non condensation)  |
| <b>DIMENSIONS</b>           | Physical          | 445mm (W) x 424mm (H) x 465mm (D)   |
| <b>WEIGHT</b>               | Net               | 18.0kg  |
| <b>PLUG &amp; PLAY</b>      |                   | DDC1, DDC2B   |
| <b>REGULATIONS</b>          |                   | CCC, MPR II, SASO, CB   |
| <b>POWER MANAGEMENT</b>     |                   | Meets MPR II  |
| <b>WARRANTY</b>             |                   | Please see:<br><a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>   |

**ViewSonic Europe Limited/UK**  
ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +32 056/85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 54 06 40 70  
Tel: +34 (0) 91 63 05 339  
Tel: +971 (0) 4 88 11 871  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. VS-E96f+SB 11/05-UK