PJD6211

Versatile, Portable XGA DLP Projector

120HZ, 3D-READY

Price/performance leader in portable DLP projectors.

ViewSonic's PJD6211 DLP® projector is ideal for use in the office or on the road. It delivers amazingly clear images with the digital clarity of DLP's BrilliantColor™ technology. This budget-friendly projector boasts amazingly fast 120Hz frame rate and is 3D ready for commercial 3D applications and 3D games at home. With high contrast ratio, brightness and ViewMatch™ technology to adjust colors perfectly, your presentations will be rich, vibrant regardless of the setting. Multiple preset presentation modes, an increased ±40 degree digital keystone correction and powerful 1.2x optical zoom ensure the best possible image regardless of location. With up to 5000 hours of lamp life, low cost replacement lamps, filter-less design and a non-degrading DLP light engine, the PJD6211 has one of the best "TOTAL COST OF PROJECTION" ratios in the industry.



OUTSTANDING PRESENTATIONS

> Bright in virtually any setting

Packs 2500 ANSI lumens in just 2.6kgs, and with a high 2000:1 contrast ratio (typ), your presentations are guaranteed to be vibrant even in the brightest office environment.

> BrilliantColorTM technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.

> Low total cost of ownership

Make the most of your projector investment with long life lamps with up to 5000 hours lamp life and a filter-less dust resistant design that reduces maintenance costs.

> Protect your investment

Assign a PIN code to password protect the projector from unauthorized use or theft.

> The perfect setup convenience

The automatic vertical keystone correction (+/- 40 degrees), aspect ratio adjustment and powerful 1.2x optical zoom ensures a perfect image in any room. Adjustable feet let you adjust the image at even higher viewing angles.

> Industry leading warranty

Enjoy full peace of mind with a generous 3 years on-site product warranty and a limited one year lamp warranty.

















PJD6211



Model No.VS12618

Versatile, Portable XGA DLP Projector







Optional Accessories

Replacement lamp	RLC-050
Wireless presentation gateway	WPG-350
Universal Ceiling Mount	WMK-018
Extended 3-year lamp warranty	LSWPY3
Universal soft case	PJ-CASE-001

	ection tance	4:3 Screen Screen Size Wide Tele			
M	feet	m	inch	m	inch
1.5	4.92	0.99	38.85	0.89	35
1.8	5.90	1.18	46.62	1.07	42
2	6.56	1.32	51.80	1.19	47
3	9.84	1.97	77.70	1.79	70
5	16.40	3.29	129.51	2.98	117
10	32.80	6.58	259.01	5.95	234







ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution

DISPLAY	Туре	0.55" Digital Micromirror Device (DLP™)	
	Resolution	XGA 1024×768 (Native) / SXGA 1280×1024 (compressed)	
	Lens	1.2× Manual optical zoom/ Manual optical focus	

Keystone Vertical digital keystone correction: ± 40 degrees 27"-300" Size

Throw Distance 1.2m-10m 1.6:1-1.9:1 Throw Ratio Lamp 180watt (RLC-050) Lamp Life 4000 / 5000 hrs Brightness 2,500 Lumens Contrast Ratio 2000:1 (with DCR)

Aspect Ratio

AUDIO

POWER

 $(W \times D \times H)$

24 bits, 16.7M Colors (8+8+8) Color Depth Color Wheel 6-Seg RGBCYW / 7200rpm Color Gamut 85 % NTSC 1931 CIE

Speaker NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and INPUT SIGNAL Computer and video

576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25pfs and 30fps)

Fh: 31-100 KHz, Fv: 50-120 Hz COMPATIBILITY PC VGA to SXGA Мас Up to 1024×768 (may require Mac Adapter)

4:3 & 16:9

CONNECTOR RGB Input 2 × 15-pin mini D-sub RGB Output 1 × 15-pin mini D-sub

1 × RCA jack Composite Input S-Video Input 1 × 4-pin mini-DIN Audio Input 1 × 3.5mm mini jack Audio Output 1 × 3.5mm mini jack

1 × RS-232 (9 Pin D-sub) 1 x type B

235W (Typical) / <1W (Stand-by mode) Consumption LANGUAGE English / Dutch / French / Spanish / Italian / Korean / Thai / Portuguese /

T. Chines / S. Chinese / Japanese / Russian / German / Swedish / Turkish / Finnish / Polish

CONTROLS POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key Basic lock, AUTO, MODE/ENTER, SOURCE

Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert.

Computer Image: Frequency, Tracking, H Position, V Position

Video Image: Saturation, Sharpnes, Tint

90~240VAC(Auto Switching), 50/60Hz (universal)

Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset, Power Saving, Auto Source, ECO Mode, High Altitude, OSD Timeout

Advance: Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shot: Digital Zoom, DCR, Close Captions, Brilliant Color

OPERATING Temperature 0°C-40°C (32°F-104°F) CONDITION Humidity 10%-90% (non-condensina) Altitude 0~6,000 ft (1,800 m), operational up to 10,000 ft (3048 m) at reduced

reliability and performance NOISE LEVEL Normal/ Eco Mode 31dB/29dB **DIMENSIONS** 280 x 114 x 218 (mm) / 11 x 4.25 x 8.58 (in) Physical

WEIGHT REGULATIONS CB_ROHS_WEEE_UL/cUL_ECC-B_ICES-003_IRAM (Argentina)_NOMPSB_

C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC WARRANTY 3-year limited warranty on parts, 1-year limited warranty on lamp

Rev.1.0

ViewSonic Europe Limited/UK

Tower 42 25 Old Broad Street London EC2N 1HQ United Kingdom

ViewSonic Germany Hanns-Martin-Schleyer-Straße 18A 47877 Willich

Germany Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers 1 allée des Bas Tilliers 92230 Gennevilliers

Tel: +33 (0) 1 41 47 49 00

ViewSonic Corporation

381 Brea Canyon Walnut California 91789-0708

Tel: +1 909 869 7976

ViewSonic Benelux Tel: +31 (0)20 491 9254 ViewSonic Denmark Tel: +358 (0)20 7120 860 ViewSonic Finland ViewSonic Norway Tel: +47 (0) 22 88 17 60 ViewSonic Spain ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

^{*}Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.
Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD6211