

PJD6221

LIGHT BRIGHT AND PORTABLE PROJECTOR

120HZ, 3D-READY

Digitally clear, dynamic presentations

The PJD6221 is a DLP® powerhouse that delivers sharp and bright images for virtually any environment. It's 3D ready with support for up to 120Hz frame rates. BrilliantColor™ technology produces more vibrant colors, while the high brightness and contrast ratio make this projector shine in the classroom or meeting room. RJ-45 connectivity enables remote network control, while the extensive input options, including two RGB inputs and one RGB output, and integrated 2-watt stereo speakers deliver a truly dynamic multimedia experience. This projector even features closed captioning for the hearing impaired. The PJD6221 is ideal for use in classrooms and corporate settings. With up to 5000 hours of lamp life, low cost replacement lamps, filter-less design and a non-degrading DLP light engine, the PJD6221 has one of the best "TOTAL COST OF PROJECTION" ratios in the industry.



> BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid color reproduction.

> Advanced connectivity

In addition to standard connectors, this projector provides two RGB inputs to easily switch between presenters and an additional RGB output to connect to an external monitor. An additional RJ45 input plus audio in/out give even more connectivity options.

> Eco-mode extends lamp life

Extend the life of your lamp up to 5000 hours** and reduce noise output.

> Network control through RJ-45

Remotely schedule, manage and monitor the projector and its lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

> Off-to-Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

PJD6221

LIGHT BRIGHT AND PORTABLE PROJECTOR



Model No.VS12472



Optional Accessories

- >Replacement lampRLC-050
- >Wireless presentation gatewayWPG-350
- >Universal ceiling mountWMK-018
- >Extended 3-year lamp warrantyLSWPY3
- >Universal soft casePJ-CASE-001

Projection Distance		4 : 3 Screen Screen Size			
		Wide		Tele	
M	feet	m	inch	m	inch
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
Tower 42
25 Old Broad Street
London EC2N 1HQ
United Kingdom

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / SXGA 1280x1024 (compressed)
	Lens	1.2x Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Display Size (diagonal)	30" -300"
	Throw Distance	1.2m-10m
	Throw Ratio	1.6:1-1.9:1
	Lamp	180watt (RLC-050)
	Lamp Life (Normal / Eco Mode)	4000 / 5000 (hours)
	Brightness	2900 Lumens
	Contrast Ratio	3000:1 (with DCR)
	Aspect Ratio	4:3 (native) & 16:9
	Color Depth	24 bits, 16.7M Colors (8+8+8)
Color Wheel	6-Seg RGBCYW / 7200rpm	
Color Gamut	85 % NTSC 1931 CIE	
AUDIO	Speaker	2W
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 31-100 KHz, Fv: 50-120 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1024x768 (may require Mac Adapter)
CONNECTOR	RGB Input	2 x 15-pin mini D-sub
	RGB Output	1 x 15-pin mini D-sub
	Composite Input	1 x RCA jack
	S-Video Input	1 x 4-pin mini-DIN
	Audio Input	1 x 3.5mm mini jack
	Audio Output	1 x 3.5mm mini jack
	Control	1xRS-232 (9 Pin D-sub) / RJ45
	POWER	Voltage
	Consumption	235W (Typical) / <1W (Stand-by mode)
LANGUAGE		English/ Dutch/French / Spanish/Italian/ Korean/Thai/Portuguese/ T. Chines/ S. Chinese /Japanese /Russian /German /Swedish /Turkish / Finnish/Polish
CONTROLS	Basic	POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key lock, AUTO, MODE/ENTER, SOURCE
	OSD	Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert. Computer Image: Frequency, Tracking, H Position, V Position Video Image: Saturation, Sharpnes, Tint Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset,Power Saving, Auto Source, ECO Mode, High Altitude, OSD Timeout Advanc: Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shot, Digital Zoom, DCR, Close Captions, Brilliant Color.
OPERATING CONDITIONS	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~1,800m (6000ft), operational up to 3,048m (10000ft)
NOISE LEVEL	Normal / Eco Mode	31dB / 29dB
DIMENSIONS	Physical	280 x 108 x 218 (mm) / 11 x 4.25 x 8.58 (inch)
(W x H x D)		
WEIGHT	Net	2.7 kg (5.95 lb)
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKRSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp

Rev.1.0

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.
Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD6211

For more product information, visit us on the web at viewsoniceurope.com