Optiquest[®] Q201wb

20" WIDESCREEN LCD WITH SUPER-FAST 5MS VIDEO RESPONSE

Affordable widescreen performance

The Optiquest® Q201wb 20" widescreen LCD is the big screen choice for users on a budget. You won' t sacrifice performance for price with this display. It combines high brightness and contrast ratio with SUPER-FAST 5MS VIDEO RESPONSE for crystal-clear, blur free video, text and graphics. The super-high 1680x1050 resolution reduces eye fatigue and ensures text and graphics are crisp. The widescreen that lets you work in two applications or documents side-by-side, enhancing your productivity. The integrated power supply and VESA ® wall-mount compliance reduce clutter and free up valuable desktop real estate. Furnish your desktop in style with the budget-friendly, budget-friendly, feature-



Enhance your productivity

- > Super-fast 5ms video response delivers superior picture clarity
- > High brightness and contrast ratio 300cd/m2 brightness (typ) and 1000:1 contrast ratio (typ) for rich, detailed images.
- > 1680x1050 optimum resolution Incredible image detail for sharp text and graphics.
- > Stylish slim-bezel design An ultra-thin bezel lets you see more without taking up valuable desktop space
- > OnView® controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Full 20" viewable widescreen Displays a full, flat 20" viewable widescreen area with crisp detail and fully saturated color.
- > Integrated power supply
- > VESA® 75mm wall-mount compliant
- > PC and Mac® compatible





Jptiquest Q201wb ViewSonic See the difference



20" WIDESCREEN LCD WITH SUPER-FAST 5MS VIDEO RESPONSE





LCD	Туре	20" color TFT active matrix WXSGA LCD
	Display Area	17.1" horizontal x 10.7" vertical; 20.1" diagonal
	Optimum Resolution	1680x1050
	Brightness	300 cd/m2 (Typ.)
	Contrast Ratio	1000:1 (typ)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio ≥10:1
		170° horizontal, 170° vertical @ contrast ratio ≥5:1
	Response Time	5ms (typ)
	Pixel Pitch	0.258mm(H) X 0.258mm(V)
	Light Source	Long life, 40,000 hrs. (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Sync	H/V Separate (TTL)
	Frequency	Fh:30-80kHz , Fv:55-75Hz
COMPATIBILITY	PC	VGA up to 1680x1050 non-interlaced
	Мас	G3/G4/G5 up to 1680x1050
CONNECTOR	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
ERGONOMICS	Tilt	-5°/+15°
POWER	Voltage	AC 100–240V (universal), 50–60Hz (auto switch)
	Consumption	45W (typ)
CONTROLS	Basic	Power, 2, up, down, 1
	OnView	Auto image adjust, brightness, contrast, colo
		adjust (sRGB, 9300K, 6500K, 5400K, user color), H
		position, V. position, H. size, OSD position, OSD
		timeout, OSD background, fine tune, sharpness
		language, input select, recall
OPERATING	Temperature	32–104°F (0–40°C)
CONDITIONS	Humidity	20–80% (non-condensing)
DIMENSIONS	Physical (WxHxD)	486mm x 409mm x 204mm (19.1" x 16.1" x 8.0")
		486mm x 345mm x 79mm (19.1" x 13.6" x 3.1")
WEIGHT	Net	4.7 kg (10.3 lb).
REGULATIONS		UL, cUL, FCC-B, NOM, ENERGY STAR, TUV-S
		CE, ISO13406-2 Class II, WEEE, RoHS, GOST-R
		Hygenic
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please
		dispose of in accordance with local, state or federa
		laws.
POWER MANAGEMENT		ENERGY STAR standards
Wall Mount		Meet VESA (75mm X 75mm) Standards
WARRANTY		One-year limited warrranty on parts, labor and backligh

ViewSonic Europe Limited/UK

Riverside House 7th Floor 2a Southwark Bridge Road London, SE1 9HA United Kingdom Tel: +44 (0) 207 921 2200 Fax: +44 (0) 207 921 2201

ViewSonic Germany Hanns-Martin-Schleyer-Strafle 18A 47877 Willich Germany Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic France Parc des Barbanniers 1 allée des Bas Tilliers 92230 Gennevilliers France Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation 381 Brea Canyon Road Walnut California 91789-0708 USA Tel: +1 909 869 7976 Fax: +1 909 869 7958

	T 1 . 20 (0) 5 (05 0 (07
ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

1. Requires optional VESA DDC/Cl compatible graphics card. 3. Mounting options available from 3rd party suppliers. 4. May requir optional Mac adapter. 5. Some features may not be available on all inputs. Copyright © 2008, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. (04/08) Q201wb-1