

VA1932w

48cm/19" VALUE SERIES WIDESCREEN LCD DISPLAY

Super Contrast Ratio Widescreen



- > **Fast 5ms video response delivers superior picture clarity**
- > **1440 x 900 native resolution**
Incredible image detail for sharp text and graphics.
- > **100,000:1 dynamic contrast ratio (typical)**
Provides darker levels of black and better overall front-of-screen performance.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**
Prevents unauthorised changes to monitor settings and maintains your optimised image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows® 7 approved**
- > **Eco modes, to reduce operating power consumption by up to 40%**
- > **PC and Mac® compatible**

Model Name:	VA1932w	VA1932wa
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (Typ.) Dynamic Contrast Ratio Viewing Angle (CR≥10 / CR≥5) Response Time (ms) Pixel Pitch (H×V) Panel Surface Light Source (Hours) Colour Support (Millions of colours)	48cm/19" Wide Color a-Si TFT Active Matrix LCD 16:10 aspect ratio 1440 × 900 300 (Typical) 1,000:1 100,000:1 170° (V), 160° (V) 5 ms 0.2835 × 0.2835 (mm) Anti-Glare, Hard coating(3H) 50,000 Minimum 16.7 M
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) Separate, composite 24-82kHz / 50-75Hz
COMPATIBILITY	PC Mac	VGA up to 1440 × 900 Non Interlaced Mac OS up to 1440 × 900
CONNECTOR	Analogue Digital Power	1×15 pin mini D-sub 1×DVI-D Internal Power Board, 3-pin plug x1
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60 Hz 35 W Typical, 40 W Maximum ≤0.5W
ERGONOMICS	Tilt	20~-5 degrees
CONTROLS	Basic OnView / OSD	[1], [2], [PW], [Dn], [Up] Auto Image Adjust, Contrast/Brightness, Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B] Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Eco mode, Setup Menu, Language Select, Resolution Notice, OSD Position, OSD Time out, OSD Background, Auto Power Off, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 20 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	445.2 x 376.0 x 189.4 (mm) / 17.5 x 14.8 x 7.5 (in)
WEIGHT	Net (w/ stand)	3.42 kg / 7.54 lb
REGULATIONS		CB, WEEE, RoHS, REACH SVHC List, EuPWindows XP/ Vista Basic, CE, Nemko ERGO, GOST-R+Hygienic, UkrSEPRO, BSMI, PSB, C-TICK, KC, SASO
WALL MOUNT (mm)	VESA® Mount Compliant	100mm × 100mm

ViewSonic®  See the difference™

For more product information, visit us at www.viewsoniceurope.com

VSE 2010/04/29 V2