

VA1936a-LED

47cm/ 18.5" LED DISPLAY

GO LED. GO GREEN.



> Ultra-Slim Bezel

The ultra-slim bezel makes more productive use of the screen area while minimizing the image gap in multi display applications for continuous data display which enhances the visual experience with clean, minimalist borders around the active image area.

> Impressive 10,000,000:1 dynamic contrast ratio provides greater detail and definition

Provides darker black levels and better overall front-of-screen performance.

> High brightness and 10,000,000 DCR to reflect the true colour

250 nits high brightness delivers precise accurate colour to realistically display a full array of brilliant shades and hues.

> Eco-mode automatically reduces power consumption and can extend backlight life and reduce operating power consumption by up to 70%



Model Name	VA1936a-LED	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (typical) Dynamic Contrast Ratio Viewing Angle (CR \geq 10) Response Time (ms) Pixel Pitch (H \times V) Panel Surface Light Source (Hours) Colour Support (Millions of colours)	47cm/ 19"(18.5") wide Colour TFT Active Matrix LCD 16:9 aspect ratio 1366 \times 768 250 (typical) 1000:1 100,000:1 170° (H), 160° (V) 5ms (typical) 0.3 \times 0.3 (mm) Anti-Glare, Hard coating (3H) 50,000 hrs (minimum) 16.7 Millions
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync 24-82kHz / 50-75Hz
COMPATIBILITY	PC Mac	VGA up to 1366 \times 768 Non Interlaced 1366 \times 768 Non Interlaced
CONNECTOR	Analogue	1 \times 15 pin mini D-sub
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60Hz(Switch) 25 (typical) / 30(miximum) \leq 0.5
CONTROLS	Basic OnView / OSD	[1], [2], Power, Down[▼], Up[▲] Auto Image Adjust/Contrast/Brightness/Audio Adjust Volume, Mute/Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B] Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Eco mode, Setup Menu/Language Select, Resolution Notice, OSD Position, OSD Time out, OSD Background, Auto Power Off, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / - 4 - 140 (°F) 20 - 90 (%)
DIMENSIONS (W \times H \times D)	Physical (w/ stand)	447.8 \times 334.2 \times 159.8 (mm)
WEIGHT	Net (w/ stand)	2.45 kg
REGULATIONS		CB, WEEE, RoHS, REACH SVHC List, Nemko ERGO, GOST-R+Hygienic, UkrSEPRO, TCO 5.0BSMI, PSB, C-TICK, SASO, CCC, CE, NOM

For more product information, visit us at www.viewsoniceurope.com

VSE17/08/2011

ViewSonic®
See the difference™ 