

VA2626wm

**25.5" VALUE SERIES
WIDESCREEN LCD**

WITH 5MS VIDEO RESPONSE

Feature-rich big screen.

ViewSonic's 25.5" VA2626wm LCD brings high-performance, widescreen displays to home office users, students and others who want a great desktop display. In addition to 1920x1200 resolution, this big 26-inch LCD also features EXTREME CLARITY, AMAZING COLOR and FAST 5MS CLEARMOTIV® VIDEO RESPONSE. Enjoy beautiful graphics and view spreadsheets in unbelievable clarity. Enhance your desktop with the stylish, slim-bezel design and enhance your productivity with the ability to VIEW TWO FULL-SIZE DOCUMENTS SIDE-BY-SIDE or work in multiple applications simultaneously on the widescreen display. Only 3.6" deep without the stand this display's VESA® wall-mount compliance allows the VA2626wm to fit beautifully into any office décor. Desktop users can enjoy panoramic performance without breaking their budgets.



ENHANCE YOUR VIEW AND PRODUCTIVITY

- > **Fast 5ms video response delivers superior picture quality**
- > **Full 25.5" viewable widescreen**
Displays a full, flat 25.5" viewable area with crisp detail and fully saturated color.
- > **1920x1200 native resolution**
Incredible image detail for sharp text and graphics.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **OSD/power lock secures your settings**
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



ViewSonic®
See the difference™ 

VA2626wm

ViewSonic®
See the difference™ 

25.5" VALUE SERIES WIDESCREEN LCD WITH 5MS VIDEO RESPONSE



ViewSonic Europe Limited/UK
Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom
Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14028-00B-05/08] VA2626wm-1

LCD	Type	25.5" color TFT active matrix WUXGA LCD
	Display Area (W x H mm)	550 x 344mm, 21.7." horizontal x 13.5." vertical; 25.5" diagonal
	Optimum Resolution	1920x1200
	Contrast Ratio	800:1 static (typ), 3,000:1 DCR
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio >10:1 170° horizontal, 170° vertical @ contrast ratio >5:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (min)
	Brightness	350 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D (HDCP) / HDMI
	Frequency	Fh: 24~82kHz, Fv: 50~85Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
	Mac®	Power Mac™ G3/G4/G5 up to 1920x1200
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D, 19-pin HDMI
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	64W (typ); below 1W in standby mode
AUDIO	Speakers	2x2.5 watts
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode, aspect ratio and ECO mode), setup menu etc.), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
ERGONOMICS	Tilt	-5°/+20°
OPERATING	Temperature	41~95°F (5~35°C)
CONDITIONS	Humidity	20~80% (non-condensing)
DIMENSIONS	Physical with stand	596mm x 480mm x 254mm (23.5" x 18.9" x 10.0")
(W x H x D)	Physical without stand	596mm x 406mm x 93mm (23.5" x 16.0" x 3.6")
WEIGHT	Net with stand	7.4 kg(16.3 lb.)
	Net without stand	5.6 kg(12.3 lb.)
	Gross with stand	10.1 kg(22.2 lb.)
REGULATIONS		UL, cUL, FCC-B, CB, CE, NOM, IRAM, NEMKO/ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR®, PSB, CTICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, video cable, audio cable, power cable, Quick Start Guide, ViewSonic Wizard (DVI and HDMI cables not included)
WARRANTY		Please see http://www.viewsoniceurope.com/UK/Support/warranty.htm

For more product information, visit us on the web at ViewSonicEurope.com