VA703b

17" VA SERIES LCD MONITOR WITH 5MS VIDEO RESPONSE

Reliable performance in a stylish design

No matter if you use it for entertainment in the home or for intensive graphics tasks, ViewSonic's 17" VA703b fits the bill perfectly. Thanks to an 5ms video response time, depictions of movies, games or scrolling text will impress with their smooth, full-motion. A 700:1 contrast ratio (typ.) and 300 cd/m² of brightness (typ.) lends this elegantly-designed model great display quality in vivid, true-to-life colour. Screen adjustments are child's play via the OSD and can be safely locked in. This slim bezel LCD is VESA compliant – it will also look great mounted on your wall. In addition, Kensington security port theft deterrence will ensure your investment is effectively protected. The VA703b LCD display provides outstanding performance for any application.

It's not just a great value LCD. It's a ViewSonic.



IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

- > ClearMotiv[®] 5ms video response time
 Super-fast 5ms video response delivers broadcast-quality full motion video.
- > Dynamic Structure™ technology Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- Very-high brightness and contrast 300cd/m² brightness (typ.) and 700:1 contrast ratio (typ.) for rich, detailed images.
- Full 17" Viewable screen with 1280 x 1024 resolution Displays a full, flat 17" viewable area with crisp details and fully saturated colours.
- > Stylish slim-bezel design

An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

- OnView[®] controls for superior screen adjustability
 Screen adjustments are precisely made via an easy-to-use on-screen menu.
- OSD/Power lock secures your settings
 Prevents changes to monitor settings and maintains an optimised image.
- > Integrated power supply
- > VESA® 100mm wall mount interface and Kensington® security port
- > PC and Mac[®] compatible
- > TCO'03 and ENERGY STAR® qualified



VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES





VA703b

17" VA SERIES LCD MONITOR WITH 5MS VIDEO RESPONSE







LCD	Type Display Area Pixel Pitch Optimum Resolution Pixel Clock Contrast Ratio Viewing Angle Response Time Colour Support Light Source Brightness Panel Surface	17" TN colour TFT active matrix SXGA LCD 33.8cm horizontal x 27.0cm vertical; 43.2cm diagonal 0.264mm 1280 x 1024@60Hz 135MHz 700:1 (typ.) 160° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1) 5ms (off-on-off) (typ.) 16.7M colours supported (6-bit + 2-bit FRC) Long life, 50000 hrs. (min.) 300cd/m² (typ.) Anti-glare (3H)
VIDEO INPUT	Analogue Frequency Synchronisation	RGB analogue (0.7 Vp-p, 75 ohm) F _h : 30–82kHz, F _v : 50–75Hz H/V separate (TTL)
COMPATIBILITY	PC Mac ¹	VGA up to 1280 x 1024 non-interlaced (@60Hz preferred) Power Mac™ up to 1280 x 1024 non-interlaced (@60Hz preferred)
CONNECTOR	Analogue Power	15-pin mini D-Sub (attached cable) 3-pin AC plug (CEE22)
POWER	Voltage Consumption	AC 100–240V, 50/60Hz (auto switch), internal power supply <36 watt (max.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic OSD	Power, menu [1], up, down, select [2] Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language [English, Finnish, French, German, Italian, Japanese, Spanish, Simplified Chinese, Traditional Chinese], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITONS	Temperature Humidity	0°C–40°C 10%–90% (non-condensation)
DIMENSIONS	(W x H x D mm)	379 x 400 x 210 (with stand)
WEIGHT	Net Gross	3.6kg (with stand) 4.8kg
REGULATIONS		TCO'03, CE, CB, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), UL/cUL, FCC-B, NOM, GOST-R, ENERGY STAR, BSMI, CCC, (PSB), (C- TICK), Green Mark, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR standards
SECURITY		Kensington security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

WARRANTY

ViewSonic Europe Limited/UK

Riverside House 7th Floor 2a Southwark Bridge Road London, SE1 9HA United Kingdom Tel: +44 (0) 207 921 2200

Fax: +44 (0) 207 921 2201

Hanns-Martin-Schleyer-Straße 18A 47877 Willich Germany

ViewSonic Germany

Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10 ViewSonic France Parc des Barbanniers 1 allée des Bas Tilliers 92230 Gennevilliers France Tel: +33 (0) 1 41 47 49 00

Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation 381 Brea Canyon Road Walnut California 91789-0708 USA Tel: +1 909 869 7976 Fax: +1 909 869 7958

ViewSonic Belux ViewSonic Denmark ViewSonic Finland ViewSonic MEA ViewSonic Netherlands ViewSonic Norway ViewSonic Spain ViewSonic Sweden

Tel: +32 (0)56 85 26 27 Tel: +45 70 22 11 71 Tel: +358 (0)20 7120 860 Tel: +971 (0) 4 88 11 871 Tel: +31 (0)20 491 9254 Tel: +47 (0) 22 88 17 60 Tel: +34 (0) 91 63 05 339 Tel: +46 (0) 8 50 71 30 00

¹May require optional Mac adapter. Copyright © 2007, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VA703b-3 10/07-UK

For more product information, visit us on the web at www.ViewSonicEurope.com