

VS13021

43cm/17" LCD displays

Affordability without compromise



- > **1280 x 1024 performance for unsurpassed viewing**
- > **ClearMotiv™ Technology**
250 nits high brightness delivers precise accurate color to realistically display a full array of brilliant shades and hues.
- > **AutoTune™ Function**
Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.
- > **OSD / Power Lock Function**
Eco-mode automatically reduces power consumption and can extend backlight life and reduce operating power consumption by up to 40%.
- > **TCO 5.0 Certified**

Model Name	VS13021	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (Typ.) Viewing Angle (CR _{≥10} / CR _{≥5}) Response Time (ms) Pixel Pitch (H×V) Panel Surface Light Source (Hours) Color Support (Millions of colours)	17" Color TFT Active Matrix LCD 1280×1024 250 (typical) Panel 1000:1(Typ.);DCR 6000:1(Typ.) 160° (H), 160° (V) 5 (typical) 0.264 x 0.264 (mm) Anti-Glare, Hard coating (3H) 50,000 (minimum) 16.7 Millions
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync 24–82kHz / 50–75Hz
COMPATIBILITY	PC Mac	VGA up to 1280×1024 Non Interlaced 1280×1024 Non Interlaced
CONNECTOR	Analogue Power	1×15 pin mini D-sub Built-in power Adapter, 3-Pin plug
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60Hz(Switch) 19W (typical) / 20.5W (maximum) ≤1W
CONTROLS	Basic OnView / OSD	[1], [2], Power, Down[▼], Up[▲] Auto Image Adjust, Contrast/Brightness, Color Adjust, sRGB, 9300K, 6500K, 5400K, User Color [R, G, B], Information, Manual Image Adjust H/V Position, Horizontal Size, Fine Tune, Sharpness, Setup Menu Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, OSD Pivot, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 10 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	379 × 400 × 210 (mm) / 14.92 × 15.75 × 8.27 (in)
WEIGHT	Net (w/ stand)	4.03 kg / 8.88 lb
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, TCO 5.0, ICES-003B, ISO13406-2, TUV/GS, TUV ERGO (covers ISO13406-2 & MPRII), TUV-S, NOM, GOST-R, HYGIENIC (20 copies), Energy Star, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS, TCO 5.0
WALL MOUNT (mm)	VESA® Mount Compliant	100 × 100