

VA903m

19" VA SERIES LCD MONITOR
WITH MULTIMEDIA

High quality, high performance.

The 19" ViewSonic VA903m is the all-in-one price performance solution for all needs. No matter if your use is for entertainment or for intensive graphics, whether in the home or in the office, the VA903m fits the bill perfectly. Its 5ms response time delivers crisp images and fluid full-motion video for games, movies and scrolling-text. Matched with high 700:1 contrast levels and 300cd/m² brightness, the VA903m displays brilliant, vivid, true-to-life colours. Invisible built-in speakers deliver true multimedia performance. The slim styling and silver-black bezel add to the monitors appeal. Prepare to be impressed by the performance, quality and style of the VA903m.

It's not just a great value LCD. It's a ViewSonic.



IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

- > **ClearMotiv™ 5ms video response time**
Super fast 5ms video response delivers broadcast-quality full motion video.
- > **Multimedia enhanced**
Save workspace and enjoy rich sound with built-in invisible stereo speakers.
- > **High brightness and contrast**
300cd/m² brightness (typ.) and 700:1 contrast ratio (typ.) for rich, detailed images.
- > **Full 19" – Viewable screen with 1280 x 1024 resolution**
Displays a full, flat 19" viewable area with crisp details and fully saturated colours.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **OSD/Power lock secures your settings**
Prevents changes to monitor settings and maintains an optimised image.
- > **Integrated power supply**
- > **VESA® 100mm wall mount interface and Kensington® security port**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



ViewSonic® See the difference™ 

VA903m

19" VA SERIES LCD MONITOR WITH MULTIMEDIA



FSM-49187 EMS-49968
I Sistemi di Gestione Qualità e Gestione Ambiente
di ViewSonic Corporation sono stati certificati
ISO 9001 e ISO 14001 dalla British Standards Institution.



LCD	Type	19" TN colour TFT active matrix SXGA LCD
	Display Area	37.6cm horizontal x 30.1cm vertical; 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angle	150° horizontal, 135° vertical (at 10:1) 160° horizontal, 150° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.7M colours supported (6-bit+2-bit FRC)
	Light Source	Long life, 50000 hrs. (typ.)
	Brightness	300cd/m ²
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Frequency	F _v : 30 – 82kHz, F _h : 50 – 85Hz
	Synchronisation	H/V separate (TTL)
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced (@60Hz preferred)
	Mac ^{®1}	Power Mac™ up to 1280 x 1024 non-interlaced (@60Hz preferred)
CONNECTOR	Analogue	15-pin mini D-Sub (attached cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2 x 1 watt integrated invisible stereo speakers
POWER	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	<35 watt (max.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, audio adjust (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language [English, Finnish, French, German, Italian, Japanese, Spanish, Simplified Chinese, Traditional Chinese], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensation)
DIMENSIONS	(W x H x D mm)	416 x 428 x 210 (with stand)
WEIGHT	Net	4.6kg (with stand)
	Gross	5.8kg
REGULATIONS		TCO'03, CE, CB, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), UL/cUL, ENERGY STAR, FCC-B, NOM, GOST-R, BSMI, CCC, (PSB), (C-TICK), Green Mark, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)20 7120 860
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.