

# Digital performance and ergonomic adjustability

The 19" ViewSonic VG930m LCD monitor is the ultimate value LCD business display. Featuring height adjustment, tilt and 360° swivel features, the VG930m allows the user to set the ergonomic position of the monitor to generate the best possible viewing position and greatest viewing comfort. Image quality is guaranteed with premium contrast and brightness levels to deliver superb pictures with vivid, brilliant colours and crisp detail. Digital and analogue inputs ensure maximum connectivity and integrated stereo speakers provide space-saving high quality sound to your desktop. The full featured VG930m is the ideal LCD monitor for business, home office, government or education use.

**It's not just a digital multimedia LCD. It's a ViewSonic**

# VG930m

**19" DIGITALMEDIA™  
LCD MONITOR  
WITH CLEARMOTIV™ 5MS VIDEO  
RESPONSE**



## ERGONOMIC PERFORMANCE FOR VISUAL EXCELLENCE

- > **Adaptable advanced ergonomics – height adjustable, tilt and 360° swivel features**  
Provides the most comfortable viewing position for the user, enabling improved image quality and improved productivity and performance.
- > **Ultra-high 1000:1 contrast ratio (typ.) and 300cd/m<sup>2</sup> brightness (typ.) levels for rich, detailed images**
- > **OptiSync® digital/analogue inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for maximum compatibility and configuration flexibility.
- > **Multimedia enhanced**  
Save workspace and enjoy rich stereo sound with built-in speakers.
- > **ClearMotiv™ 8ms video response time**  
Fast 8ms video response time delivers seamless fluid full-motion video.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Full 19" viewable screen with 1280 x 1024 resolution**
- > **TCO'03 and ENERGY START® qualified**
- > **VESA 100mm wall mount interface and Kensington® security port**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

# VG930m

## 19" DIGITALMEDIA™ LCD MONITOR WITH CLEARMOTIV™ 8MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	19" TN colour TFT active matrix SXGA LCD
	Display Area	37.6cm horizontal x 30.1cm vertical; 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	1000:1 (typ.)
	Viewing Angle	170° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.7M colours supported (6-bit+2-bit Hi-FRC)
	Light Source	Long life, 40000 hrs. (min.)
	Brightness	300cd/m <sup>2</sup>
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 24-82kHz, F <sub>V</sub> : 50-75Hz
	Synchronisation	H/V separate (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1280 x 1024 non-interlaced
	Mac <sup>®1</sup>	Power Mac™ up to 1280 x 1024 non-interlaced
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	2 x 1.5 watt integrated stereo speakers
<b>POWER</b>	Voltage	AC 100-240V, 50/60Hz (auto switch), internal power supply
	Consumption	35 watt (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
	Swivel	360° swivel base
	Height Adjustment	0-80mm
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2], mute
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), audio (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	0°C-40°C
	Humidity	10%-90% (non-condensation)
<b>DIMENSIONS</b>	(W x H x D mm)	428 x 457-537 x 230 (with stand) 428 x 399 x 68 (without stand) 486 x 590 x 278 (packaging)
<b>WEIGHT</b>	Net	6.0kg (with stand)
	Gross	7.2kg
<b>REGULATIONS</b>		TCO'03, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), CE, CB, GOST-R, PSB, ENERGY STAR, UL/cUL, FCC-B, ICES 003, SASO, BSMI, C-Tick, CCC, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'03 and ENERGY STAR® standards
<b>SECURITY</b>		Kensington® security port
<b>WALL MOUNT</b>		VESA FDMI 100mm x 100mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, D-sub video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

### ViewSonic Europe Limited/UK

ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

ViewSonic Denmark  
ViewSonic Finland  
ViewSonic Italy  
ViewSonic MEA  
ViewSonic Netherlands  
ViewSonic Norway  
ViewSonic Spain  
ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 5406 4070  
Tel: +39 02 73 95 50 22  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter.