

3500 ANSI Lumens XGA DLP Projector for Small Spaces

PA502X



Higher Brightness - Longer Lamp Life - XGA DLP Projector

The ViewSonic PA502X projector for presentations offers impressive visual performance in small sized meeting rooms and classrooms. Packed with up to 3500 ANSI lumens of brightness and a 22,000:1 contrast ratio, the PA502X projector is guaranteed to project the finest of details, even in brightly lit environments. ViewSonic's exclusive SuperColor™ technology offers wide gamut color coverage that produces true-to-life image color for realistic and engaging image projection. Users can project 3D content directly from 3D Blu-Ray players and HDMI-enabled devices. PA502X also comes with an energy efficient SuperEco feature which reduces lamp power consumption by up to 70%, and extends the lamp life to 15,000 hours on average.

- Up to 3500 ANSI lumens of brightness with a 22,000:1 contrast ratio for bright and crisp presentations
- Up to 15,000 hours of long lasting lamp life
- 3D Blu-ray ready HDMI input
- SuperColor™ technology provides amazing color performance
- Top access lamp door enables simple lamp maintenance

Impressive Performance




Bright Images in Any Environment

3,500 ANSI lumens of brightness and a 22,000:1 high contrast ratio guarantee the production of bright images in any environment, including rooms with high ambient light.




Normal



SuperColor™ Technology

Superb Color Accuracy

ViewSonic's proprietary SuperColor™ Technology displays a wide range of visible color, ensuring that users enjoy more realistic and accurate color in both bright and dark environments without sacrificing image quality.



Fine-Tuned Viewing

Choose from 5 unique preset viewing modes to provide the best settings for your usage:

- Brightest Mode: For environments where the maximum brightness is required
- Presentation Mode: High-brightness and a high contrast ratio for presentations in brightly lit environments.
- Standard Mode: Enhanced color, similar to that of a PC or Notebook.
- Photo Mode: Natural color for general viewing
- Movie Mode: Saturated color for a better movie watching experience in dark environments.



Immersive 3D Viewing

PA502X's HDMI port allows users to project 3D content directly from 3D Blu-Ray players and HDMI-enabled devices such as laptops, tablets, and media players.



1. Keypad
2. LED indicator
3. Lamp cover
4. Zoom/Focus
5. Projection Lens
6. Front IR
7. RS232
8. VGA
9. Video
10. HDMI
11. Mini USB
12. Kensington® LockSlot

Energy Efficiency



Extended Lifespan

Users can choose different lamp mode to extend the lamp's lifespan. When Power Saving setting is on and without any signal input, the projector will automatically switch to Eco Mode and SuperEco Mode

- **Eco Mode:** This projector automatically switches from Normal to Eco Mode whenever it has been left idle for 5 minutes.
- **SuperEco Mode:** When the projector has not received an input signal for 20 minutes, projected images are dimmed to 70%, extending the lamp's lifespan to 15,000 hours on average.



Automatic Sleep Timer

Forgetting to shut off projectors is a common occurrence, especially in public spaces such as classrooms and meeting rooms. PA502X's sleep timer allows you to select a period of inactivity that will determine when the projector should put itself into sleep mode automatically.



Auto Power Off

When no signal has been detected, the projector will automatically power off to conserve energy and lamp life.

User-Friendly Usage



Instant Activation

Get your projector up and running instantly with two simple settings:

- Direct Power On: Simply connect the power cord and begin; the projector will power itself on automatically.
- Signal Power On: The projector will power on automatically upon detection of a VGA cable connection.



Remote Control Functionality

This projector can be assigned to 8 different remote control codes in the same venue through a single remote control for effortless projector selection, configuration and operation during lessons or meeting. It can also operate certain projectors when the coded are fitted both on the projector and on the remote control.



Advanced Image Correction

Vertical keystone allows you to correct and adjust distorted images with ease, making installation flexible.

Smart Presentation Tools



Time Management Assistance

Presenter Timer is an embedded on-screen timer that helps users with time management during presentations. Once a specified time limit has been reached, the projector will signal this with a beep, keeping presentations running on time.



Attention Refocusing Capabilities

Using PA502X's Blank Timer, presenter can refocus the audience's attention back to them by hiding the screen's image at different points during a presentation. In addition, Blank Timer can also be used as a reminder for when to take breaks.

Caractéristiques Techniques

SPECIFICATION	Projection system	0.55" XGA
	Native Resolution	1024x768
	DC type	DC3
	Brightness	3500lm
	Contrast Ratio with SuperEco mode	22000:1
	Display Color	1.07 Billion Colors
	Light Source	Lamp

Light source life (Nor/SuperEco)	5000/15000
Lamp Watt	190W
Lens	F=2.5-2.7, f=22.08-24.28mm
Projection Offset	125%+/-5%
Throw Ratio	1.97~2.17
Image size	30" - 300"
Throw Distance	1.16m-13.42m(100" @ 3.97m)
Keystone	±40° (Vertical)
Lens Shift V. Range	NA
Lens Shift H. Range	NA
Optical Zoom	1.1x
Audible Noise (Eco)	30dB
Resolution Support	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120Hz
Interactive Camera	NA

Input

Computer in (share with component)	1
Composite	1
S-video	NA
Component (RCAX3)	NA
Audio-in (3.5mm)	NA
Audio-in (RCA R/L)	NA
Microphone in	NA
HDMI	1 (Back)
HDMI/MHL	NA
3D VESA (Sync)	NA
DVI-D	NA
5BNC	NA
SD Card	NA
USB type C	NA

Control	RS232	1	
	RJ45	NA	
	USB type mini B (Services)	1	
	USB type B (Services)	NA	
	Wired Remote Control - In	NA	
	Wired Remote Control - Out	NA	
	HDBaseT	NA	
	<hr/>		
Others	Power Supply Voltage	100-240V+/- 10%, 50/60Hz AC	
	Power Consumption	Normal: 240W Standby: <0.5W	
	Operating Temperature	0~40°C	
	Carton	Brown	
	Net Weight	2.1kg	
	Dimensions (WxDxH) w/adjustment foot	320x209.8x122.7mm	
	Language	Anglais, français, espagnol, thaï, coréen, allemand, italien, russe, suédois, néerlandais, polonais, tchèque, chinois traditionnel, chinois simplifié, japonais, turque, portugais, finlandais, indonésien, hindi, arabe, vietnamien	
	<hr/>		
Standard Accessory	Power Cord	1	
	HDMI Cable	NA	
	VGA cable	1	
	Remote Control	1	
	QSG & CD	QSG: 1 / CD: NA	
	Lens Cover	NA	
	Air Filter	NA	
	Cable Management	NA	
	Wall Mount	NA	
	Interactive Software	NA	
	<hr/>		

Pour en savoir plus, rendez-vous sur : www.viewsoniceurope.com

Tous droits réservés par Copyright ViewSonic Corporation. Tous autres noms de sociétés et marques sont propriété de leurs sociétés respectives. E&EO. Les caractéristiques techniques et prix susceptibles de modifications sans préavis. Les images peuvent être utilisées seulement à des fins d'illustration. Pour en savoir plus consulter nos dispositions légales.