

# Optiquest® Q191wb

19" WIDESCREEN LCD

WITH SUPER-FAST  
5MS VIDEO RESPONSE

## Widescreen enhances productivity.

The Optiquest® Q191wb 19" widescreen LCD enhances your productivity because it lets you work in two applications or documents side-by-side. Enjoy the crystal-clear, blur-free video and graphics delivered by broadcast-quality, 5ms video response. High brightness and contrast ratios ensure your colors are rich and vibrant. The integrated power supply and VESA® wall-mount compliance reduce clutter and free up valuable desktop real estate. The OSD lock ensures your screen settings are secure and the Kensington® security port provides theft deterrence. Furnish your workplace in style with the budget-friendly, feature-rich Q191wb LCD.



- > **Super-fast 5ms video response delivers superior picture clarity**
- > **High brightness and contrast ratio**  
300 cd/m<sup>2</sup> (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > **1440x900 optimum resolution**  
Incredible image detail for sharp text and graphics.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop space.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Full 19" viewable widescreen**  
Displays a full, flat 19" viewable widescreen area with crisp detail and fully saturated color.
- > **Integrated power supply**
- > **VESA® 75mm wall-mount compliant**
- > **PC and Mac® compatible**



**ViewSonic®**  
See the difference™ 

# Optiquest® Q191wb

19" WIDESCREEN LCD  
WITH SUPER-FAST 5MS VIDEO RESPONSE



<b>LCD</b>	Type	19" color TFT active matrix WXGA LCD
	Display Area	410mm W x 256mm H, 16.16"
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 (typ)
	Viewing Angles	150° horizontal, 130° vertical @ contrast ratio ≥ 10:1 160° horizontal, 150° vertical @ contrast ratio ≥ 5:1
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	300 cd/m <sup>2</sup> (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	Fh: 30~65kHz, Fv: 55~75Hz
	Sync	H/V separated (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac®**	G3/G4/G5 up to 1440x900
<b>CONNECTOR</b>	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
<b>ERGONOMICS</b>	Tilt	20 ~ -5 degrees
<b>POWER</b>	Voltage	AC 100~240V (universal), 50~60Hz (auto switch)
	Consumption	35W (typ)
<b>CONTROLS</b>	Basic	Power, 2, up, down, 1
	OnView®	Auto image adjust, brightness, contrast, color adjust (sRGB, 9300K, 6500K, 5400K, user color), H. position, V. position, H. size, resolution notice, OSD position, OSD timeout, OSD background, fine tune, sharpness, language, recall
<b>OPERATING CONDITIONS</b>	Temperature	41~95°F (5~40°C)
<b>DIMENSIONS (W x H x D)</b>	Physical with stand	464mm x 383mm x 169mm (18.3" x 15.1" x 6.7")
	Physical without stand	464mm x 309mm x 58mm (18.3" x 12.2" x 2.3")
<b>WEIGHT</b>	Net with stand	4.2 kg (9.2 lb.)
	Net without stand	3.4 kg (7.5 lb.)
	Gross with stand	5.3 kg (11.7 lb.)
<b>REGULATIONS</b>		UL, cUL, FCC-B, NOM, ENERGY STAR®, TUV-S, ISO13406-2 Class II, CE, WEEE, RoHS, GOST-R / Hygienic The lamp in this product contains mercury.
<b>RECYCLE/DISPOSAL</b>		Please dispose of in accordance with local, state or federal laws. ENERGY STAR® standards
<b>POWER MANAGEMENT</b>		LCD display, power cable, video cable, User Guide
<b>PACKAGE CONTENTS</b>		One-year limited warranty on parts, labor and backlight
<b>WARRANTY</b>		



**ViewSonic Europe Limited/UK**  
Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom  
Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany  
Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France  
Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA  
Tel: +1 909 869 7976  
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

\*\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [13756-00B-04/08] Q191wb-3

For more product information, visit us on the web at [ViewSonicEurope.com](http://ViewSonicEurope.com)