

Optiquest® Q241wb

24" WIDESCREEN LCD WITH
SUPER-FAST 5MS VIDEO
RESPONSE

Work and play on the big screen

The Optiquest® Q241wb 24" widescreen LCD is the big screen choice for users on a budget. The super-high 1920x1200 resolution produces brilliantly crisp text and graphics. With 400 cd/m² brightness (typ), 800:1 contrast ratio (typ) and SUPER-FAST 5MS VIDEO RESPONSE, you'll enjoy crystal-clear, blur free video, text and graphics.

The widescreen lets you work in two applications or documents side-by-side, ENHANCING YOUR PRODUCTIVITY. The integrated power supply and VESA® wall-mount compliance reduce clutter and free up valuable desktop real estate. The Q241wb is perfect for the serious professional, gamer or digital entertainment enthusiast on a budget.



ENHANCE YOUR DESKTOP EXPERIENCE

- > **Super-fast 5ms video response delivers superior picture clarity**
- > **High brightness and contrast ratio**
400cd/m² brightness (typ) and 800:1 contrast ratio (typ) for rich, detailed images.
- > **1920x1200 optimum resolution**
Incredible image detail for sharp text and graphics.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop space.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu
- > **Full 24" viewable widescreen**
Displays a full, flat 24" viewable widescreen area with crisp detail and fully saturated colour.
- > **Integrated power supply**
- > **VESA® 75mm wall-mount compliant**
- > **PC and Mac® compatible**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

Optquest® Q241wb

ViewSonic®
See the difference™ 

24" WIDESCREEN LCD WITH SUPER-FAST 5MS VIDEO RESPONSE



LCD	Type	24" color TFT active matrix WUXGA LCD
	Display Area	20.4" horizontal x 12.8" vertical; 24.0" diagonal
	Optimum Resolution	1920x1200
	Brightness	400 cd/m2 (Typ.)
	Contrast Ratio	800:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio ≥ 10:1 170° horizontal, 170° vertical @ contrast ratio ≥ 5:1
	Response Time	5ms (typ)
	Pixel Pitch	0.270mm(H) X 0.270mm(V)
	Light Source	Long life, 40,000 hrs. (typ)
	Panel Surface	Anti-glare
	VIDEO INPUT	Analog
Sync		H/V Separate (TTL)
Frequency		FH : 30-80kHz , Fv : 56-60Hz
COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
	Mac	G3/G4/G5 up to 1920x1200
CONNECTOR	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
ERGONOMICS	Tilt	-5°/+15°
POWER	Voltage	AC 100–240V (universal), 50–60Hz (auto switch)
	Consumption	85W (typ)
AUDIO	Speakers	2x2 watt
CONTROLS	Basic	Power, 2, up, down, 1
	OnView	Auto image adjust, brightness, contrast, color adjust (sRGB, 9300K, 6500K, 5400K, user color), H. position, V. position, H. size, OSD position, OSD timeout, OSD background, fine tune, sharpness, language, input select, recall
OPERATING CONDITIONS	Temperature	32–104°F (0–40°C)
	Humidity	20–80% (non-condensing)
DIMENSIONS	Physical (WxHxD)	570mm x 463mm x 260mm (22.4" x 18.2" x 10.2") 570mm x 400mm x 103mm (22.4" x 15.8" x 4.0")
	WEIGHT	Net
	Net without stand	5.3kg (11.7 lb).
	Gross with stand	7.3kg (16.1 lb).
REGULATIONS		UL, cUL, FCC-B, NOM, ENERGY STAR , TUV-SC, ISO13406-2 Class II, WEEE, RoHS, GOST-R / Hygenic
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		ENERGY STAR standards
PACKAGE CONTENTS		LCD display, power cable, video cable, audio cable, User Guide
Wall Mount		Meet VESA (75mm X 75mm) Standards
WARRANTY		One-year limited warranty on parts, labor and backlight

ViewSonic Europe Limited/UK
Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom
Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

1. Requires optional VESA DDC/CI compatible graphics card. 3. Mounting options available from 3rd party suppliers. 4. May require optional Mac adapter. 5. Some features may not be available on all inputs.
Copyright © 2008, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies (04/08) Q241wb-1.

For more product information, visit us on the web at ViewSonicEurope.com