



Overview

The ViewSonic® SC-Z55 Zero Client is the perfect solution for companies seeking a seamless desktop experience with ultra-high security and reliability in networks based on VMware® technology networks. This is a true Zero Client device and features no local memory or moving parts for the ultimate in energy savings and reliability. Based on the Teradici™ Tera 2321, with hardware accelerated PCoIP,™ the VMware® certified design guarantees performance and compatibility in your network. Dual video outputs provide flexibility for supporting dual 1080p digital displays, and the eco-friendly design consumes up to 90% less energy than standard PCs. The SC-Z55 is also a space saver—its 0.6L form factor easily attaches to your VESA-ready monitor with an included VESA mounting bracket. ViewSonic's Zero Clients are the smart choice for optimising your virtual desktop deployment.

True Personal PC Experience



**Optimized Power for VMware®
View**

Para más información sobre nuestros productos, visite www.viewsoniceurope.com

Todos los derechos reservados por ViewSonic Corporation. Todos los otros nombres corporativos y marcas registradas son propiedad de sus respectivas compañías. E&EO. Las especificaciones y precios pueden ser modificados sin previo aviso. Las imágenes son solo para fines ilustrativos. Para más información consulte nuestras condiciones de uso.



The SC-Z55 supports 2D and 3D graphic-intensive applications and a rich multimedia experience at full frame rates over Gigabit Ethernet. This is the no-compromise solution for demanding users.

Easy Deployment and Management

Deploy users up to 5-times faster than traditional PC-based clients, and enjoy on going simplified management without the need for constant patches and system updates.



Simplified and Secure Management

The Teradici PCoIP Management Console provides for centralised deployment and management. With web-based access, administrators will be able to configure, update, manage, and even remotely control the power state for all of their PCoIP-based zero clients throughout the network.

Teradici's Tera2321 is the most advanced processor for VMware-based virtualization. Experience all of your applications with an ultra-fast response time.

Dual Display Productivity

With dual digital outputs, the SC-Z55 supports either two 1080p displays, or one QHD (2560x1600) display for increased productivity.



Low Total Cost of Ownership

All of the benefits of a virtual desktop deployment can be realised with ViewSonic's SC-Z55 Zero Client. From simple and quick deployment, enhanced security with no local HDD, increased reliability and higher productivity—the SC-Z55 is an efficient and low-cost choice for virtualizing desktops.



Technical Specifications

DIMENSIONS	Physical With Stand	1.6 x 5.6 x 4.1 in. / 39.5 x 143 x 103 mm
	Packaging	7.9 x 5.0 x 6.2 in. / 200 x 128 x 157 mm
REGULATIONS	FCC/NRTL, ENERGY STAR®, EPEAT Silver, WEEE, RoHS, REACH	
PACKAGE CONTENTS	SC-Z55 Zero Client, power cord, power adapter, DVI-I to VGA adapter, Stand/VESA mounting bracket, Quick Start Guide, ViewSonic Wizard CD	
	**Actual content may differ from market to market	

WARRANTY

Para más información sobre nuestros productos, visite www.viewsoniceurope.com

Todos los derechos reservados por ViewSonic Corporation. Todos los otros nombres corporativos y marcas registradas son propiedad de sus respectivas compañías. E&EO. Las especificaciones y precios pueden ser modificados sin previo aviso. Las imágenes son solo para fines ilustrativos. Para más información consulte nuestras condiciones de uso.

3-year limited warranty on parts and labour

**Warranty offered may differ from market to market

CONNECTOR	Video Output	DVI-D (x1), DVI-I (x1)
	USB	USB 2.0 (x2 front, x2 rear)
	Headphone	3.5mm mini jack (x1)
	LAN	RJ45 (x1)
	Power	DC In
	Microphone in	3.5mm mini jack (x1)
POWER	Voltage	5V DC; 3A, 15W
	Consumption	7W (typ)
VESA® MOUNT		100mm x 100mm
MEMORY	System	DDR3 512MB @ 1066MHz
CORE	CPU	Teradici Tera 2321
GRAPHICS	Resolution	1920x1200 (dual display) 2560x1600 (single display with optional Dual Link DVI adapter)
COMMUNICATION	Ethernet LAN	10/100/1000 MB
SOFTWARE	Protocols	PCoIP (Hardware accelerated)
	Management	ViewSonic Device Manager / ViewSonic Client Setup
	Network Standard	Gigabit Ethernet
WEIGHT	Gross	2.5 lb. / 1.1 kg
	Net	1.2 lb. / 0.5 kg
OPERATING CONDITIONS	Humidity	10–90% (non-condensing)
	Temperature	32–104°F (0–40°C)
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state or federal laws
COUNTRY OF ORIGIN		Taiwan

Para más información sobre nuestros productos, visite www.viewsoniceurope.com

Todos los derechos reservados por ViewSonic Corporation. Todos los otros nombres corporativos y marcas registradas son propiedad de sus respectivas compañías. E&EO. Las especificaciones y precios pueden ser modificados sin previo aviso. Las imágenes son solo para fines ilustrativos. Para más información consulte nuestras condiciones de uso.



ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.